# We're for better business

What we really mean to do is help you present your business information with increased impact and retention via Video projection with the GE PJ500 large screen television projector.

Video display used to mean a small monitor designed for an audience of approximately 5 to 20 persons. Or, several monitors scattered around a room to accommodate a large group.

No longer. Your business information can now take on new meaning and. understanding when viewed on a single large screen from two to twenty feet wide



in brilliant natural color. One large focal point for attention and impact.

A GE PJ500 Color Video Projector can be the most vital component in your information system for data presentation. Coupled to your computer facilities, it can project Alpha-numeric and graphic displays and computer generated images, in real time, for instant review. Information necessary for management decisions, to assess planning alternatives and measure business results.

The PJ500 can also be employed in presenting a wide variety of other business communications such as personnel training, plant safety programs, new product introductions, operations review, advertising and sales promotion programs.

For input, the projector's versatility includes the ability to display information from all standard video sources, such as Off-Air TV reception, Video Tape, and Video Cassette, live Camera, Closedcircuit TV. Data Network and Video Film Chain.

For output, GE's exclusive "single gun" single optical path system generates the complete range of spectral colors simultaneously. The resultant inherent color registration insures optimum results with both front and rear screen projection applications.

Its compact size allows it to be moved easily from your training center, to your boardroom, or to an auditorium for a stock holder's meeting. And, it operates from standard 115v/20 amp appliance outlets.

GE large screen television projectors are warranted for one year to be free of defective

# **GE large screen** television projectors

materials or workmanship. The "single gun" light valve and projector lamp are warranted for 1000 hours or one year on a prorated basis.



For more information on improving your business information system. look into the GE PJ500, or its monochrome counterpart, the GE PJ700, today.

Call (315) 456-2562 or write to:



Video Display Equipment Operation General Electric Company **Electronics Park** Syracuse, New York 13201







Application of the Laminar Flow Gun to **Cathode-Ray Tubes By NORMAN H. LEHRER** 

CRT?

By JIM E. WURTZ

**Multicolor** and Multipersistence Penetration CRTs

By ANDRE MARTIN

Four Test Patterns for Vector (line drawings) Computer Displays By ROBERT M. LEE



Circle #22 on Readers Service Card



SID 1974 International Symposium and Exhibition

San Diego, California **Town & Country Hotel** 







# *syntronic*

# optimun CORNER FOCUS

Is a function of ...

- deflection angle
- Iight output
- yoke impedance
- display speed
  CRT neck diameter
- CRT length
- yoke production capability

To produce one or one hundred yokes having optimum corner focus requires a thorough knowledge of system design trade-offs.

To see the difference our 25 years of experience can make, let us focus on your yoke problem.



SYNTRONIC INSTRUMENTS, INC. 100 Industrial Road, Addison, IL 60101 Phone: (312) 543-6444

# **CAN BETTER** YOKES HELP IN THE ENERGY CRISIS?

It's interesting that when something is in the news...the oil crisis, for example...we at Syntronic learn about it, often ahead of the general public, because we make yokes. The energy crisis came along and several customers called us and asked for help. One makes a TV camera system for oil exploration on the ocean floor. It runs along down there, helps the drilling operation, looks for oil leaks. Another makes an instrument for geological charting of each foot of an oil well shaft. A precision picture on the CRT... by means of a better voke ... may help solve part of the energy crisis problem.

For 25 years, Syntronic Instruments, Inc. has been involved in the news. Do you remember what was going on in 1949? The year we were founded. The Russians exploded their first atomic bomb. NATO was established. The UN Building was dedicated, and Dr. Henry Marcy and some associates founded Syntronic Instruments, Inc. to make better vokes for CRTs.

Syntronic has grown with the times, and now makes more precision vokes than all the other yoke companies put together. It takes years to build an organization to serve the information display industry as smoothly and efficiently as we do. Here's how we work. An engineer has a problem. We struggle with an idea, making something a little special to suit his need. Next, he may want 10 pieces to perform just like the prototype. Then 100 or 1,000. We have the production flexibility and the know-how to make one part or a thousand. We have the whole package ... ideas and good, repetitive products-yokes, coils, accessories, assemblies.

It's this kind of service that led to our being named "Midwest Supplier of the Year" in 1973 by the Small **Business Administration.** 

If you have a display problem, ask us to put our 25 years of experience to work for you.

# *syntronic*

# YOKE PROBLEM SOLVERS

Which deflection voke should you use?

We constantly find new design concepts to resolve yoke problems for display engineers. Ask Syntronic for a recommendation on your application.

SYNTRONIC INSTRUMENTS, INC. 100 Industrial Rd., Addisor Phone: (312) 543-6444





# Application of the

Consideration is given t laminar flow gun versus which has been virtually for the past 40 years.

> 60-Plus Papers Set f Program

It has been suggested (v adherents to the cult of cathode ray tube is on it **Monkeying Around** 

Multicolo

Coloring coding improv response time. However only black-and-white pi CRT development has b rather than scientific or

Four Test Patterns for

The author suggests us graphics displays not re tests provided by the m

CLOSING DATES: Editorial closing date is the first of the month preceding month of issue. Advertising closing date is the 15th of the month preceding date of issue. SUBSCRIPTIONS: U.S., its territories and Canada \$10.00 per year. \$18.00 for 2 years. Foreign

Countries \$20.00 per year. EDITORIAL CONTRIBUTIONS: All material must be accompanied by stamped return enve-lopes. While all reasonable care will be taken with editorial submissions the publisher assumes no responsibility for art work, manuscripts or photographs. sumes no responsibility for art w pyright 1972 by The Society for Society for Information Display. postage paid at Los Angeles. Cali

THE OFFICIAL JOURNAL OF THE SOCIETY FOR INFORMATION DISPLAY. Published bimonthly by Blackwent Publishing Company, 1605 Cahuenga Boulevard, Los Angeles, California 90028, 213/463-4891. Correspondence regarding advertising, reprints and subscriptions should be sent to the above address.

Publisher, Robert Black/Editor, Erwin A. Ulbrich/Editorial Coordinator, Roby Wentz/Advertising Manager, William R. Brand/Production Manager, Joyce Wallace/Circulation Manager, S. Rocklin.

SID NATIONAL OFFICERS: President, Dr. Carlo P. Crocetti/Vice President, Robert C. Klein/ Secretary, Erwin A. Ulbrich/Treasurer, B. J. Lechner.

National Office Manager . . . Violet Puff

e Laminar Flow Gun to Cathode-Ray Tubes o the merits of the the cross-over gun the CRT standard	7	By NORMAN H. LEHRER
or San Diego SID Meet	14	
1974 SID International		
ymposium & Exhibition	17	
Whither the CRT?	20	By JIM E. WURTZ
with an assist from 'newness') that the ts way out.		
in the Display Industry	26	
r and Multipersistence Penetration CRTs	30	By ANDRE MARTIN
ves recognition and r, must CRT's show ctures. Most color been for color TV, industrial applications.		
or Vector (line arawing) Computer Displays	35	By ROBERT M. LEE
ers of computer ely entirely upon nanufacturer.		
<b>President's Message</b>	4	
<b>New Products</b>	24	
<b>Sustaining Members</b>	39	
Sid Activities	43	
<b>Advertisers Index</b>	46	
Sustaining Members	46	





# **CAMERA NEWS** 2 INCH PLUMBICON



IN THE PRODUCTION OF AN ULTRA HIGH RESOLUTION CAMERA FOR THE MOST DEMANDING TV NEEDS

# **ULTRA-HIGH RESOLUTION**

2000 TV LINES LIMITING 1000 TV LINES@ 50% MODULATION

# 

VARIABLE: LINE RATES **ASPECT RATIO** INTERLACE

# BROAD GREY SCALE

10 to 15/2 SHADES OF GREY

# LOW DISTORTION

**GEOMETRIC LESS THAN 1%** SHADING LESS THAN 5% AT ALL SIGNAL LEVELS

# WIDE BANDWIDTH

65 MHz STANDARD 90 MHz SPECIAL

# **PACKAGED FOR YOUR** NEEDS

LABORATORY TELESCOPE O.E.M. SIMULATORS RUGGEDIZED DATA PROCESSING SEQUENTIAL COLOR LOW LEVEL LIGHT

# SRL Delivers What Others Are Trying To Develop

# AND SRL MAKES THE TV MONITORS TO MATCH

FOR ADVANCED VIDEO REQUIREMENTS, CONTACT THE ELECTRO-OPTICAL IMAGING SPECIALIST

ELECTRONIC IMAGE SYSTEMS GROUP SYSTEMS RESEARCH LABORATORIES, INC. 0 INDIAN RIPPLE ROAD, DAYTON, OHIO 45440 LEPHONE (513) 426-6000

Circle #2 on Readers Service Card

A professional society such as ours should and must provide a variety of services to its membership if it is to fulfill its role of fostering improved avenues toward increased professionalism of its individual members. There are many vehicles by which such a role can be fulfilled among which are publications, symposia and technical meetings. standards, recognition by means of awards of significant achievements and the encouragement of chapter activities. Your National Officers and your Board of Directors are, and have been, fully aware of their need to strive continuously to improve all aspects of the value of your membership in the Society. In a small society such as ours, however, in which our resources are limited and in which we depend so heavily upon the voluntary activities of dedicated people who also have other jobs, we have, unfortunately, not been able to do everything at once.

For that reason, your Board has, in the past, put primary effort upon two areas of activity, that is, publications and technical meetings. In both areas we shall continue to improve our activities. For example, we are exploring means of sponsoring Fall technical meetings on each coast in alternate years with other technical societies in order to stress the inter-disciplinary nature of our Society.

I believe, however, that our Society's efforts in these two areas have reached the point that we can all take pride in the professionalism which these activities foster. The efforts of your National Board can now turn to other areas for which we have a responsibility as National Officers to improve. Of particular concern to me has been the aid which the National can and should provide to our Chapters.

In many ways, this is a complex problem. A number of our Chapters have been vigorous and energetic in providing their membership with opportunities for local technical activities. Others, however, have faced serious problems in providing for viable Chapter activities and in meeting the necessary administrative obligations associated with the operation of a Chapter. Your Board has already had some discussions about possible methods of improving this situation. We are most anxious to exchange local technical activities, and yet we recognize that the geographic areas covered by some chapters makes it difficult to meaningfully schedule events for all members. We have considered many approaches, including the possibility of providing small subsidies to any group of our members to conduct technical meetings even if not under the aegis of a formal Chapter organization. Since I believe that this area of local professional activities is the next most pressing matter deserving the attention of your Board, I am most anxious to hear from any of you, particularly those not realistically participants of existing chapters, about ideas you may have.

> Dr. Carlo P. Crocetti President

EDITORIAL BOARD: Chairman, Erwin A. Ulbrich, McDonnell-Douglas Astronautics/Thomas V. Curran Information Displays, Inc./George Kaelin, Motorola, Inc./Violet Puff, Society for Information Display, A. H. Wisdom, TRW Systems Group. SID National Headquarters/654 N. Sepulveda/Los Angeles, Calif. 90049/Tel. 213/472-3550

# can improve the performance of your CRT's.



Watkins-Johnson—U.S.A.: 3333 Hillview Ave., Palo Alto, CA 94304 • (415) 493-4141 • TWX: 910-373-1253 • Telex: 34-8415 • Cable: WJPLA • 700 Quince Orchard Rd., Gaithersburg, MD 20760 • (301) 948-7550 • TWX: 710-828-0546 • Telex: 89-8402 • Cable: WJCEI • United Kingdom: Shirley Ave., Windsor, Berkshire SL4 SJU, England • Tel: Windsor 69241 • Cable: WJUKW-WINDSOR • Telex: 847578 • West Germany: 8033 Planegg, Muenchenerstr. 17 • Tel: (089) 859-9441 • Cable: WJDBM-Muenchen • Telex: (841) 529401 • Italy: Piazza G. Marconi, 25 00144 Roma-EUR • Tel: 59 45 54 • Cable: WJROM-ROMA • Telex: (843) 60117





If you have a brightness, resolution or grid drive problem for special display applications, W-J may have the solution.

The Laminarflo gun design concept can be advantageously applied to all types of CRT's, including magnetic deflection-electrostatic focus, magnetic deflection-magnetic focus and electrostatic focus and deflection types.

Visit Booth 203 at SID 74 and get the details on W-J's family of Laminarflo CRT's. Or. call Watkins-Johnson Applications Engineering at (415) 493-4141 to discuss your specific new tube design or CRT replacement requirements.





# **OCLI Antireflection Coatings** Improve the View... nearly everywhere.

It all started with a need to reduce the glare from aircraft instrument covers. Working closely with the U.S. Air Force, OCLI designed and developed a multilayer state-of-the-art coating that reduced reflections five times better than a single layer of MgF2. For several years now pilots have been able to read their instruments with ease through covers

coated by OCLI and our licensees. A most satisfying development, but that was only the beginning. Today descendants of that coating, each modified to do a specific job, are improving the view in a lot of places.

If you are having trouble with reflections, ghost images, poor visibility, we can probably help you. If yours is a stubborn problem and you



let us in at the beginning, chances are you'll benefit from working with our research scientists and design engineers. Try us. We supply more than just a product.

**OPTICAL COATING** LABORATORY, INC. **Technical Products Division** 2789 Giffen Ave., P.O. Box 1599, Santa Rosa, CA 95403 Teletype 510-744-2083. Telephone 707-545-6440.

Manufacturing facilities serving Europe, OCLI Optical Coatings, Ltd., Dunfermline, Fife, Scotland / Represented in Japan by Hakuto Co., Ltd., Tokyo; France, Belgium, Netherlands and Luxembourg by Techmation of Paris, Brussels & Amsterdam; and in Germany, Austria, Switzerland and Italy by Betzelt GMBH, Munich.

Circle #4 on Readers Service Card



Consideration is given to the merits of the laminar flow gun versus the crossover gun which has been virtually the CRT standard for the past 40 years.

■ The ultimate objective in the design of a CRT electron gun is usually the achievement of a tube with the highest resolution and brightest spot with the least power, and longest life-time and smallest volume for any given display area.

For approximately the past 40 years, this objective has been satisfied by the crossover electron gun (References 1-4) as evidenced by the fact that almost every CRT produced incorporates such a gun. Recently, David J. Bates and

Aris Silzars (References 5, 6 and

# Figure 1. Concentrating optical system

Figure 2. Crossover gun electron trajectories

Figure 3. Laminar flow gun electron traiectories



### By NORMAN H. LEHRER

7) indicated that a laminar flow gun is capable of superior performance to that of the crossover gun. The work reported here is an application to CRT electron guns of the laminar flow concepts disclosed and advocated by them.

# **Conceptual Comparison between Crossover and Laminar Flow Guns**

The function of the electron gun is to provide a small intense spot of controllable brightness on the phosphor viewing screen. This spot should be as small as possible and as bright as possible to provide an optimum display.

In the simplest sense, the electron gun is analogous to an optical system which produces an intense image of a bright object. As illustrated in Figure 1, a bright source serves as the object for the convergent glass lens which focuses its image into a small spot. In the optical case, image brightness is dependent on source intensity and distribution. Within limits, this is also true for electron guns. The crossover gun attempts to provide an intense source by shaping the electric field lines in the vicinity of the cathode so that the electrons are converged to a crossover almost immediately upon leaving the cathode. It is this crossover which is the object that is imaged on the phosphor screen. To produce this crossover, the electric field is very high at the center of the cathode and falls off rapidly with radial distance. The emission density, in a gross sense, is conicallike in shape, assuming a circular cathode. This conical distribution is converged into a crossover and then re-imaged on the viewing screen as shown in Figure 2. Of course, the intensity distribution at the cathode is reflected in the crossover and ultimately in the spot on the screen, Thus, even with an ideal imaging system, the best that can be achieved is a spot with an intense center, surrounded by a region of lesser intensity, rapidly decreasing with radius. Passing the beam through an aperture can improve the uniformity of the Figure 4. Photograph of 8" CRT

spot by masking the outermost portion of the beam. This requires increased signal strength (grid drive), however, since more cathode current must be provided to compensate for the reduced current to the screen.

In contrast, in the laminar flow gun (Figure 3), the electric field across the surface of the cathode is relatively uniform. The electrons emitted from the cathode tend to flow in streamline paths until they are converged to a focus at the viewing screen. Because of the shape of the electric field lines, the emission density across the cathode is relatively constant and may be considered for comparative purposes to have the shape of a cylinder. Thus, for the same peak cathode loading, in the ideal case, the laminar flow gun can provide three times the current density from the same cathode area. (The volume of the cylinder is three times the volume of a cone.) This means it can provide the same total emission from a cathode region 60% of the diameter of the crossover gun, therefore achieving a 40% reduction in the diameter of the emitting region. Alternately, for a given beam current and emitter diameter, the peak cathode loading will be considerably lower in the laminar flow gun.

The energy distribution of the electrons also affects the resolution.

Electrons with energy components transverse to the tube axis move radially from their origin as they proceed toward the viewing screen. These transverse velocities cause a spreading of the image on the screen.

Of course, electrons are emitted from the cathode with a certain energy distribution. In the case of the crossover gun, the aberrations present in short focal length lenses further degrade the energy distribution. The use of longer focal length lenses which have less aberrations in the cathode region of the laminar flow gun reduce this degradation.

Space-charge, or the mutual repulsion of electrons, is another factor which limits resolution. Such space-charge repulsion can occur in the crossover and as the beam is brought to a focus at the viewing screen. By eliminating the crossover, the laminar flow gun avoids one space-charge source of degradation.

The basic design of the laminar flow gun is such that it has a higher perveance (transconductance) than the crossover gun, that is, any given change in electrode voltage produces a larger charge in cathode current.

# Advantages of the Laminar Flow Gun

The basic advantages of the laminar flow gun compared to a



# ANNOUNCING COMTAL 8000 DIGITAL IMAGE **PROCESSING SYSTEM**

The new 8000 permits you to pictorialize the problem—be it in plant operations, energy re-search and development, medical or industrial X-ray work, law enforcement, weather anal-ysis, earth resources study, and hundreds more. Working directly with a computer or as a stand alone system the versatile 8000 creates exciting new opportunities for the solution of many critical problems.





# By NORMAN H. LEHRER

crossover gun are as follows:

- 1) Two to three times stronger source intensity due to more uniform cathode loading.
- 2) Lower noise (normal velocity components) in beam because of reduced lens aberrations.
- 3) Avoidance of space-charge limitations in crossover.
- 4) Higher transconductance, that is, a larger change in cathode current for a given change in grid voltage.

These characteristics can improve the performance of a CRT in several ways, although, not necessarily all at the same time. Trade-offs between the improvements may be possible.

1) Resolution: Because factors such as space-charge in the beam. electron energy distribution and lens aberrations limit the resolution as well as source intensity, the anticipated improvement in spot size is less than the reduction in the size of the source. As much as a 30% reduction in spot size, or double the current density in the spot at the screen, appears as a reasonable expectation when a crossover gun is replaced with its direct replacement laminar flow gun. By "direct-replacement" is meant that the laminar flow gun is the same length and width as the crossover gun and operates at the same voltage. The importance of comparing direct replacement guns is discussed in the next section.

2) Higher Brightness: The brightness of a phosphor generally increases with current density of the exciting electron beam over a wide range of densities. The increased brightness is not always directly proportional to the current density because of saturation effects in the phosphor. Depending upon the phosphor and the current density, the ability of the laminar flow gun to produce an increase of two times the current could result in a similar increase in the peak line brightness without a corresponding reduction in resolution.

3) Reduced Grid Base: The higher transconductance of the laminar flow gun means that for

the same charge in grid potential, much larger screen currents can be produced. This permits either a reduction in the amplitude of the signals to the tube or a brighter picture for the same signal level.

# **Direct-Replacement CRT Electron Guns**

Several parameters determine the condition under which the optimum spot size is achieved. These include:

- 1) Viewing screen potential 2) Focus potential (for electrostatic focus tubes)
- 3) G2 potential



- 5) Gun length and diameter
- 6) Tube length
- 7) Current efficiency (ratio of screen current to cathode current)
- 8) Cathode loading

A comparison of electron gun performance (resolution) must be based on consideration of all those parameters which characterize the gun. Thus, it is usually possible to improve the resolution of any given gun by lengthening its focus structure. This improved resolution is obtained at the expense of



Figure 5. 8" CRT schematic



Figure 6. Crossover gun schematic

tube length and generally current efficiency, since less of the cathode current reaches the screen. This lengthened gun is not actually better than the shortened gun because it gives higher resolution, but rather different because it has been optimized for a different set of parameters.

A truly superior gun would be one that exhibits improved resolution without trading off any of the parameters. Such an improved gun would yield improved performance (better resolution) under the same conditions as an existing gun and would serve as a direct replacement for it without any change in the physical or electrical parameters that describe the display system. It is this criteria that has been applied in comparing the laminar flow gun with a crossover gun.

# Comparison of a Crossover Gun CRT with its **Direct-Replacement Laminar Flow Gun CRT**

The concept of the laminar flow gun design can be advantageously applied to all types of CRT's including magnetic deflection-electrostatic focus, magnetic deflection -magnetic focus and electrostatic focus and deflection.

As pointed out previously, in order to obtain a meaningful evaluation of the laminar flow gun, its performance must be compared with that of a crossover gun CRT for which it is a direct replacement.

As a starting point, the crossover gun tube chosen was an 8" high resolution 70° deflection electrostatic focus-magnetic deflection device. This particular tube was selected because it represented a significant effort on the part of another organization to develop a high resolution 8" CRT.

A photograph of the 8" tube incorporating the laminar flow gun is shown in Figure 4. Of course, the 8" tube with the crossover gun has an identical appearance. A schematic of the tube is shown in Figure 5. The crossover gun is shown in Figure 6.

Using this crossover gun design as a starting point, a direct-replacement laminar flow gun was developed. The laminar flow gun developed employed different electrode shapes but the electrode diameters, focus electrode and overall

gun lengths were identical. One significant change that had to be made was a reduction in the size of the final aperture from .075" to .050". This had to be done to achieve the same current efficiency in both guns at 30µA screen current. The following data was obtained on the tubes using a single slit analyzer technique. In the following tables and discussion, the laminar flow gun tube is identified by "LFG Tube" and the crossover gun tube by "COG Tube".

# Tube

COG Tube LFG Tube

For both tubes, the screen potential was 12 KV and the focus potential about 2000 volts. The writing speed was 10 microseconds per inch with a 60 hertz repetition rate. Examination of the above data indicates that the LFG tube has 30% more resolution and less than ½ the cut-off voltage of the COG tube. By raising the G2 potential so that the cut-off voltage is the same as that of the COG tube, the resolution of the LFG tube becomes almost twice that of the COG tube.

shown below:

Tube

COG Tube LFG Tube

Note that at a G2 potential of 300 volts, the current efficiency (screen current divided by cathode current) is comparable for both tubes even though the exit aperture is 30% smaller in diameter for the LFG tube. This means, gun can produce twice the current density in the final aperture than

# By NORMAN H. LEHRER

the crossover gun. This should produce about a 30% decrease in the deflection defocusing which is proportional to the beam bundle diameter. (In the case of electrostatic deflection tubes it may mean up to twice the brightness plus higher current efficiency.) The grid drive is only 15 volts for the

Cathode	Screen	G-2	G-1 Cut-Off	Spot Size Inches		
Current (µA)	Current (µA)	Potential (Volts)	Potential (Volts)	to 50%	to 100%	
68	30	300	-70	.0057	.0142	
65	30	300	-30	.0040	.0037	
85	30	916	-70	.0030	.0082	

There are other comparisons that can be made between the COG tube and the LFG tube as

laminar flow gun as opposed to 26 volts for the crossover gun.

Increasing the G2 potential to 916 volts on the laminar flow gun makes the cut-off voltage at -70volts, the same as that of the crossover gun. The resolution of the laminar flow gun is almost twice that of the crossover gun but the current efficiency of the laminar flow gun is now only 35% as opposed to 46% for the crossover gun. The grid base of the laminar flow gun at 24 volts is still shorter than that of the crossover gun if only by 2 volts. Note that the "0" bias current for the laminar flow gun is about 50% greater than that of the crossover gun when the cut-

Exit Aperture Diameter Inches	Cathode Current (µA)	Screen Current (µA)	G-2 Potential (Volts)	Grid Drive for 30 µA Screen Current (Volts)	0 Bias Current mA
.070	68	30	300	26	1.7
.050	65	30	300	15	0.65
050	85	30	916	24	2.6 +

offs are equal. This higher value of "0" bias current results in a much shorter grid base for the laminar flow gun and permits corresponding reductions in video drive requirements when cathode modulation is used. Space-charge limitain this case, that the laminar flow tions are theoretically encountered at lower values of beam current or the exit aperture is reduced in size.

# By NORMAN H. LEHRER

Thus, the use of a smaller exit aperture in the laminar flow gun would suggest at a sufficiently high value of beam current, the resolution of the crossover gun would be better than that of the laminar flow gun. However, this would only be true if the spacecharge limitation in the crossover is small compared to those in the beam after it leaves the final aperture.

Although data for only one value of cathode and screen current is presented here, similar results were obtained over a wide range.

# Conclusion

The basic design concept of the laminar flow gun appears to offer improvements over the crossover gun. These include more intense and uniform source, lower beam noise, avoidance of space-charge in crossover and a higher perveance structure. Although this paper reports on only one type of CRT,



Figure 7. Typical trace width profile. Vertical scale: arbitrary intensity units. Horizontal scale: Distance, 0.00355 inches/cm

these advantages can probably be 2. Hillary Moss, "Electron Gun of the translated into many types of CRT's with higher resolution, increased brightness and reduced grid drive requirements. Furthermore, these improved CRT's can be direct physical and electrical replacements for existing CRT's using crossover guns.

# **Acknowledgements**

The work described in this paper was conducted at the Watkins-



Johnson Company, Tube Division, Palo Alto, California. Alan I. Dawes made a major contribution to the results reported in this paper. Richard Franseen (Night Vision Laboratories, Fort Belvoir, Virginia), Paul Decker (formerly of the Night Vision Laboratories) and Waldo R. Robinson (Naval Electronic Laboratory Center, San Diego, California) also contributed to this work.

# References

- Maloff and Epstein, "Electron Optics in Television", McGraw-Hill Book Company, 1938 (New York), pp. 118-123.
- Cathode Ray Tube", Part I Journal of the British Institution of Radio Engineers, dated January 1945.
- Hillary Moss, "Electron Gun of the Cathode Ray Tube", Part II Journal of the British Institution of Radio Engineers, June 1946.
- 4. Hillary Moss, "Engineering Methods in the Design of the Cathode Ray Tube", Journal of the British Institution of Radio Engineers, dated January 1945.
- 5. Silzars and Bates, U.S. Patent No. 3,740,607-Laminar Flow Electron Gun and Method.
- 6. L. A. Roberts, David J. Bates, Aris Silzars and James A. Long: "Design and Performance of Deflected-Beam Electron Bombarded Semiconductor Amplifiers", IEEE Trans. Vol. ED-20, pp. 439-447, April 1973.
- 7. A. Silzars, D. J. Bates and A. B. Ilanoff: "Electron Bombarded Semiconductor Devices", Proc. IEEE (to be published).

# **GE World Service**

General Electric was to feature its globe-spanning MARK III Information Services in its exhibit at the National Computer Conference, Chicago, May 6-10. A complete data processing service, MARK III provides timesharing, networking and remote batch computer services to customers through the world's largest commercial computer network.

Composed of more than 100 interconnected communications and data processing computers, GE's MARK III Information Services network spans 17 time zones and is available in more than 360 cities in the U.S., Canada, Western Europe, Japan and Australia. It is accessed by local telephone call from more than 90% of the free world's business telephones.



Our color CRT's enable the viewer to accurately discriminate between modes of operation, or classes of symbols. Large numbers of complex bits can also be presented and comprehended without confusion. Superior brilliance and contrast is achieved by varving the voltage of a single electron beam scanning a multiphosphor screen. Resolution is comparable to that of high quality monochrome



# DuMont puts a brighter light in your multicolor displays.

CRT's, DuMont's penetration design, however, eliminates the complicated convergence circuitry employed in conventional four color displays. Current applications utilizing our multiphosphor screen CRT's include transportation control (air and surface), biomedical research, critical path analysis, process flow charting and photographic and map interpretation. DuMont multiphosphor screen

Circle #7 on Readers Service Card

technology is also being adopted to multipersistence penetration screens to add variable persistence capability to radar presentations. Tell us about your particular color CRT requirements. For our new brochure contact: Marketing Department, DuMont Electron Tubes and Devices Corporation, 750 Bloomfield Avenue, Clifton, New Jersey 07015 (201)773-2000.

See us at SID, Booths #106-107

# **60-Plus Papers Set For San Diego SID Meet**

A great program, reflecting the most advanced substantially the same as the one beginning on Page worldwide developments in the field of information display design and applications, will be presented during the 1974 International Symposium and Exhibition, May 21-23. This year's International Symposium will be held in the setting of the beautiful Town and Country Hotel in suburban San Diego, California.

As this issue of SID JOURNAL closed, the program was not totally finalized; but as can be seen on Page 17. Symposium registrants will have access to more than 60 papers in the field, prepared by more than 200 specialists in the United States, Europe and the Far East.

Among highlights will be early development reports on video disc technology; a session on visual flight simulation; a luncheon talk on bioluminescence; and an opening-session invitational address on the evolution of the shadow-mask TV tube.

Chairman H. Gene Slottow advises that the popular 2-day seminars, introduced at San Francisco during the 1972 Symposium, will be continued under the cosponsorship of SID and University of California/ Berkeley.

The annual 3-day exhibition of operational equipment, components and systems, for information display uses will be held with the Symposium at the Town and Country Hotel.

As in the past, 800-1,000 word illustrated condensations of all program presentations will be available at the meeting and will be distributed to all registrants (additional copies will also be on sale, \$15.00 to SID members, \$20.00 to non-members. Advance programs,

17, but probably with some changes, are available from the SID National Office, 654 N. Sepulveda Bl., Los Angeles, CA 90049; phone Area 213-472-3550; or from Lewis Winner, 152 W. 42nd St., New York, N.Y. 10036, phone 212-279-3125.

Registration can be accomplished as follows: (1) By mail, in advance, to SID 74, P.O. Box 3357, Anaheim, California 92803. Advance registrations postmarked before May 14, are \$30 for SID members, \$40 for non-members. (2) At the Symposium, Town & Country Hotel, San Diego, California, is \$40 for members, \$50 for non-members. Special rates apply to students. To reserve sleeping accommodations, write direct to the Town & Country Hotel. Registration can also be accomplished by using card in this issue of SID Journal.

Chairman of the 1974 Symposium is H. Gene Slottow, Owens-Illinois. Other 1974 Symposium officials are: Secretary, Joseph Markin, Zenith Radio; Treasurer, Robert C. Knepper, Hughes Aircraft; in charge of Technical Program, Samuel M. Stone, GTE Laboratories; Program Secretary, Verne J. Fowler, GTE Laboratories; Advisor on Overseas Program and overseas contributors, Rudi S. Engelbrecht, RCA/Zurich; in charge of local (San Diego) arrangements, Richard E. Thoman, General Dynamics Electronics; in charge of Awards, John L. Simonds, Eastman Kodak; in charge of Special Events, John B. Flannery, Xerox.

Symposium Consultant/Exhibit Manager is Lewis Winner, of Lewis Winner/Consultants, 152 W. 42nd St., New York, N.Y. 10036.

# **AMA Talk Concerns Computer Auditing**

Computer auditing software programs which enables security checks was discussed by Joseph J. Wasserman, president of Computer Audit Systems, Inc., of East Orange, N.J., at a recent conference of the American Management Association, at the Americana Hotel in New York.

Wasserman, whose talk covered "Data Security and EDP Auditing," also discussed implementing effective data security in the corporation.

Auditing packages, Wasserman stated, give the auditor complete independence from his programming staff. "They enable the auditor to gather accurate audit data in a fraction of the time once required. If used properly, they permit the auditor to select data that requires further analysis and this ultimately will provide management with more meaningful audit reports."

Wasserman also discussed evaluation and selection of audit packages, auditing on-line, real-time systems, computer security and EDP auditing techniques.

# **Computers and Law** Theme of Book

A new, softcover book "Computers, Society and the Law: the Role of Legal Education" has been published by the American Federation of Information Processing Societies (AFIPS). The 270-page bookedited by Joseph E. Leininger, Associate Dean of the Stanford Law School, and Bruce Gilchrist, Director of Computing Activities at Columbia University-contains major presentations, papers and discussions from an invitational conference held June 25-27, 1973 at the Stanford Center for Research and Development in Teaching, Palo Alto, Ca.

The conference, sponsored by the Stanford Law School and AFIPS. brought together 91 lawyers, legal educators and leading computer experts to analyze how computers and computer-related material should be introduced into legal education.

Copies may be ordered at \$6.00 per copy from AFIPS Press, 210 Summit Avenue, Montvale, New Jersey 07645.

According to Gilchrist, "The major thrust of the conference and the resulting proceedings is directed to determining what should be included about computers in legal education. Our aim has been to pull together in one volume a comprehensive overview of immediate value to those in the legal profession, legal educators and computer scientists concerned with the impact of computers on society. We believe this book provides one of the most authoritative sources of information on current activity at the interface between computers and the law."

# comes with RCA ultra-high resolution CRT's...

Because RCA specifically designs, develops and builds these precision CRT's-from phosphor to electron gun -for Computer Output on Microfilm applications. RCA types like the fiveinch C24125 and the seven-inch 4506 can achieve ultra-high resolution with a line width less than 0.0009 inch between the 50% points on the line profile. The phosphor RCA produces for

these tubes is responsible for much of their outstanding performance. It has a spectral distribution that achieves excellent energy coupling to ultra-finegrain photographic emulsions. And it is applied to the faceplate by special techniques that assure particle sizes

INTERNATIONAL SALES OFFICES: ARGENTINA-Casilla de Correo 4400, Buenos Aires/BRAZIL-Caixa Postal 8460, São Paulo/CANADA-21001 No. Service Rd., Ste. Anne de Bellevue 810 Quebec/ENGLAND-Sunbury-on-Thames, Middlesex/HONG KONG-P.O. Box 112/MEXICO-Apartado 17-570, Mexico 17, D.F./SWITZERLAND-118 rue de Rhone CH1204, Genevi

compatible with the ultra-fine electron beam spot created by the electron gun. The result is a highly uniform phosphor screen free from mottling and other defects that interfere with high quality recording.

There are many more reasons why RCA ultra-high resolution CRT's perform so well in COM and other photographic reproduction applications. Your RCA Representative will be glad to give you more information on them. See him today or contact: Manager, Market Planning, Display Tube Prod-ucts, Section ZD8, RCA, New Holland Ave., Lancaster, Pa. 17604. Telephone (717) 397-7661 TWX 717-560-4403.



Digesting the extraordinary capabilities of Ramtek's new color graphic display systems is a little like turning a nine-year-old loose in a candy factory.

There's almost too much to swallow.

So let's take it one morsel at a time.

To begin with, Ramtek series Color Graphic Display Systems totally obsolete conventional process control display methods. You've seen, or are now working with, the archaic bank of meters, the slow tedious strip charts and the space taking plot boards.

All those techniques are now "out of it" with the introduction of Ramtek's solid state Color Graphics System. Our basic system begins with black and white alphanumeric display. Flicker-free color graphics and animated displays are created by using a non interlaced repeat field at 60 frames/sec, thus making a real time reporting system a reality.

Perhaps the most important features of our new systems are their flexibility and expandability. Our graphic systems feature multiple channel input and varying mixtures of resolution. The system is totally adaptable to the specific and changing needs of the user.

There's lots more to be said about our systems. Contact us for a demonstration of the potential savings in cost and time between a Ramtek Color Graphic Display and any combination of conventional display techniques.

Or, for some rather startling information about our new systems, contact: Ramtek Corporation, 292 Commercial Street, Sunnyvale, California 94086. Telephone: (408) 735-8400.

RANTEK

RAMTEK CORPORATION

THE GRAPHIC DISPLAY COMPANY



MAY 21-22-23, 1974



MONDAY **20** Senate-Committee Rooms

ALL DAY 9:00 am - 4:30 pm

SID UNIVERSITY OF CALIFORNIA SEMINAR

TUESDAY 21 San Diego Room

Formal Opening MORNING 9:00 am - 9:45 am Welcoming Remarks H. G. Slottow General Chairman, SID 74 S. M. Stone Program Chairman, SID 74 Annual SID Business Meeting

C. P. Crocetti President, SID L. Beiser Chairman, SID Honors and Awards Committee H. G. Slottow

SID Honors and Awards Presentations 1973 Symposium Best-Paper Awards

2 San Diego Room

2.1 Invited

TUESDAY

MORNING 10:30 am - 12:10 pm **DISPLAY DEVICES** 

& TECHNIQUES Chairman D, E. LIDDLE Xerox Palo Alto Research Center Palo Alto, Cal. **Computer Graphics with Realtime Dynamics** K. F. KRAIB Meckenheim, W. Germany

3.1 A Digital 4 x 4 Matrix-Multiplier for Forschungsinstitut fur Anthropotechnik

Source Coding as an Aid to Optimal Display Terminal Design J. J. O'REILLY

University of Essex Essex, England 3.3 A Dual Gun Scan Converter Tube with Organic Film Storage Target T. NIŠHINO AND H. MAEDA Matsushita Research Institute Tokyo, Inc.

# 1974 INTERNATIONAL SYMPOSIUM and EXHIBITION SAN DIEGO, CALIFORNIA, TOWN AND COUNTRY HOTEL

# MORNING 9:00 am - 12:10 pm

**OPENING SESSION** INVITED ADDRESS Chairman H. G. SLOTTOW University of Illinois Urbana, III.

DEVELOPMENT OF THE SHADOW-MASK COLOR PICTURE TUBE Edward W. Herold Consultant

Ikuta Kawasaki, Japan

3.4 A Stretched Segment LED Display G. T. IKARI, R. H. HAITZ, P. JEUNG AND R. SOLOMON Hewlett-Packard Co. Palo Alto, Cal.

# TUESDAY

2 Golden West Room

MORNING 10:30 am - 12:10 pm Session 4 GAS DISCHARGE DISPLAY

SYSTEM TECHNIQUES Chairman

R. L. JOHNSON University of Illinois Urbana, III.

4.1 Internal Random Access Address Decoding in an AC Plasma Display Panel

J. D. SCHERMERHORN Owens-Illinois, Inc. Perrysburg, O.

4.2 Light Pen Capability on a Plasma **Display Panel** P. D. T. NGO

Bell Telephone Laboratories, Inc. Holmdel, N.J.

4.3 Dynamic Light Pen Tracking on a Plasma Panel P. D. T. NGO AND W. H. NINKE Bell Telephone Laboratories, Inc. Holmdel, N.J.

4.4 AC Plasma Panel Television Display with 64 Discrete Intensity Levels B. C. ANDERSON AND V. FOWLER **GTE** Laboratories

Waltham, Mass. TUESDAY

2 | San Diego Room

AFTERNOON 2:00 pm - 5:10 pm Session 5 VIDEO DISC TECHNOLOGY Chairman J. MARKIN Zenith Radio Corp. Chicago, III. 5.1 A Review of Video Disc Principles A. KORPEL Zenith Radio Corp. Chicago, III. 5.2 Transmission Mode Optical Video **Disc System** R. L. WHITMAN Zenith Radio Corp. Chicago, III. 5.3 Title to come E. M. KACZOROWSKI AND J. A. JEROME I/O Metrics Corp. Sunnyvale, Cal. 5.4 Title to come G. BROUSSAUD, E. SPITZ AND C. TINET Thomson CSF Orsay, France

# **SID** 1974 International Symposium and Exhibition SAN DIEGO, CALIFORNIA, TOWN AND COUNTRY HOTEL

MAY 21-22-23, 1974

# TUESDAY

**?** Council-Chamber Rooms

EVENING 5:15 pm - 6:30 pm **Author Interviews** 

EVENING 6:00 pm - 7:30 pm Social Hour-

EVENING 8:00 pm - 11:00 pm **Panel Discussions** 

# WEDNESDAY

**77** San Diego Room

MORNING 9:00 am - 12:10 pm Session 6 LASER, HOLOGRAPHIC, AND 3-D DISPLAYS Chairman V. J. FOWLER **GTE** Laboratories Waltham, Mass.

6.1 Computer Holograms Revisited J. C. NEWELL, D. O. DICKMAN AND M. A. WINKLER University of California/Los Alamos Scientific Laboratories Los Alamos, N.M.

6.2 The Integram-The Integration of Motion Pictures into Holograms T. H. JEONG AND H. SNYDER Lake Forest College Lake Forest, Ill.

6.3 Stereoscopic Television Display for **Remote Vision** 

J. R. TEWELL AND C. E. POLHEMUS Martin Marietta Aerospace Denver, Colo.

6.4 A Three Dimensional Display for Radar Returns H. S. COLE, J. C. REICHE, D. W.

SKELLY AND C. R. STEIN General Electric Co. Schenectady, N.Y.

6.5/1 Advanced Integrated Modular Instrumentation System (AIMIS) W. G. MULLEY Naval Air Development Center Warminster, Pa.

6.5/2 Acoustooptic Deflection Display System

H. GREEN Naval Air Development Center Warminster, Pa.

6.5/3 Hologram Optics in Head-Up Displays D. H. CLOSE

Hughes Research Laboratories Malibu, Cal.

6.5/4 Holographic Multicolor Moving Map Display K. D. QUIRING Naval Air Development Center Warminster, Pa.

# WEDNESDAY

22 Golden West Room

MORNING 9:00 am - 12:10 pm Session 7 SOFTWARE AND SYSTEM TRADEOFFS Chairman

W. D. PETTY **Owens** Illinois Toledo, O. 7.1 Tradeoffs in the Design of an Intelligent Display Terminal

D. I. CAPLAN Raytheon Data Systems Norwood, Mass. 7.2 Satellite-Host Tradeoffs in

**Computer-Aided Design** J. HATVANY Hungarian Academy of Sciences Budapest, Hungary 7.3 Developing Man-to-Machine Soft-

ware with Structured Programming Techniques A. D. THOMPSON **IBM** Corporation Morris Plains, N.J. 7.4 Tutor Graphic Capabilities P. TENCZAR University of Illinois Urbana, III. 7.5 Conic Curves for Graphics

L. VILLALOBOS Hughes Aircraft Co. Oceanside, Cal. 7.6 Menus as Devices R. A. BERMAN Vector General, Inc.

# WEDNESDAY

**77** California Room

# 12:00 noon - 1:50 pm

LUNCH INVITED ADDRESS/DEMONSTRATION W. D. McELROY

Canoga Park, Cal.

# WEDNESDAY

AFTERNOON 2:00 pm - 5:30 pm Session 8

MATRIX - ADDRESSED PANELS Chairman B. KAZAN

IBM T. J. Watson Research Center Yorktown Heights, N.Y. 8.1 LED Color Display with Memory

Functions C. SUZUKI, T. UNO AND S. MITO

Sharp Corp. Central Res. Lab. Tenri City, Nara, Japan

8.2 The Thyroptor—A Gallium Phosphide LED with Integral Storage . R. PEAKER, V. PASTORE, A. MOTTRAM AND B. HAMILTON Ferranti Ltd. Oldham, England

8.3 Stable High-Brightness Thin-Film Electroluminescent Panel T. INOGUCHI, M. TAKEDA. Y. KAKIHARA, Y. NAKATA AND M. YOSHIDA Sharp Corp. Central Res. Lab.

Tenri City, Nara, Japan 8.4 TV Imaging System using Thin-Film

**Electroluminescent Panels** S. MITO, C. SUZUKI, Y. KANATANI AND M. ISE Sharp Corp. Central Res. Lab. Tenri City, Nara, Japan

8.5 Recent Progress in Electrophoretic Displays

A. L. DALISA Philips Laboratories Briarcliff Manor, N.Y.

8.6 A Low Power Single Chip Calculator using A Multiplexed Liquid Crystal Display

E. T. FITZGIBBONS AND R. G. CARLSON **Rockwell International Microelectronics** Div.

- Anaheim, Cal. 8.7 Transient Times of the Dielectric **Deformation in a Nematic Liquid**
- Crystal M. F. SCHIEKEL, K. FAHRENSCHON AND H. GRULER AEG Telefunken Donau, W. Germany

# WEDNESDAY

**77** Golden West Room

### AFTERNOON 2:00 pm - 5:30 pm Session 9

DISPLAY QUALITY - IMAGE

AND MESSAGE PERCEPTION AND CONTENT

Chairman

A. SOBEL Zenith Radio Corp.

Chicago, III.

9.1 Human Factors of Optical Displays R. S. KICKLIGHTER AND R. F. WITZEL

Eastman Kodak Co.

Rochester, N.Y. 9.2 Measuring the Information Content of Visual Scenes J. C. McKECHNIE

Naval Training Equipment Center Orlando, Fla. 9.3 Analysis of Perceived Image

Quality R. W. COHEN AND I. GOROG

**RCA** Laboratories Princeton, N.J. 9.4 Perpheral-Visual Response Time

and Visual-Display Layout Design R. F. HAINES

AMES Research Center/NASA Moffett Field, Cal.

# 9.5 Optical Characteristics of Display/ Memory Panels\* R. W. BURKE, H. J. HOEHN AND

M. E. FEIN Owens-Illinois, Inc. Perrysburg, O. 9.6 The Format and Color of Small Matrix Displays for use in High Ambient Illumination

B. ELLIS, G. J. BURRELL, J. WHART AND T. D. F. HAWKINS **Roval Aircraft Establishment** Farnborough, Hampshire, England \*Diaivue®

# WEDNESDAY

22 Council-Chambers Rooms

EVENING 6:00 pm - 7:30 pm **Author Interviews** 

# WEDNESDAY

22 San Diego Room

# EVENING 8:00 pm - 11:00 pm

Session 10 - INVITED: VISUAL FLIGHT SIMULATION Chairman W. G. GOOD General Electric Co.

Syracuse, N.Y. 10.1 Simulation/Past-Present-Future R. McLANAGHAN Redifon Flight Simulation, Ltd. Sussex, England 10.2 Computer-Generated TV Imagery B. J. SHINN General Electric Co. Daytona Beach, Fla. 10.3 Developments in Pilot Training R. A. WALDROP American Airlines

Fort Worth, Tex. THURSDAY

# 23 San Diego Room

MORNING 9:00 am - 12:10 pm Session 11 GAS DISCHARGED DEVICES Chairman I. REINGOLD US Army Electronics Command Ft. Monmouth, N.J. 11.1 Xenon-Based Gas Mixtures for **Phosphor Panels\*** D. C. HINSON Owens-Illinois, Inc. Perrysburg, O. R. A. BENNETT Owens-Illinois, Inc. Toledo, O. 11.2 Color-TV Display Using a Flat Gas-**Discharge Panel** M. FUKUSHIMA, S. MURAYAMA AND T. KAJI Hitachi Central Res. Lab. Tokyo, Japan

Displays F. WALTERS Ferranti Ltd. Oldham, Lancs., England **Display Panel** C. D. LUSTIG, A. W. BAIRD AND H. VERON Sperry Research Center Sudbury, Mass. J. B. ARMSTRONG AND G. WATTS Beckman Instruments, Inc. Scottsdale, Ariz.

11.4 The Multilayer Gas-Discharge

11.5 32-Inch Graphic Plasma Display Module B. A. STROM Control Data Corp. Minneapolis, Minn. 11.6 Single Substrate AC Plasma

Display

\*Digivue®

# THURSDAY 23 Golden West Room

Session 12

Chairman S. SHERR North Hills Associates Glen Cove, N.Y. J. J. DePALMA Eastman Kodak Co. Rochester, N.Y. Y. G. HURD L. E. Carpenter & Co. Norwalk, Conn. H. O. PEPRNIK Ferranti-Packard Ltd. Toronto, Ont., Canada D. B. HAKEWESSELL Conrac Corp. Duarte, Cal. K. W. PIETROWSKI Xerox Corp. Webster, N.Y. STEPHANY Xerox Corp. Webster, N.Y.

of Projection Display Screens Display Development **Thickness and Dielectric Constant** for the *\gamma***-RUTICON Class of Liquid Crystal Display** 

LARGE AREA DISPLAYS **12.1 INVITED: Optical Characteristics** 12.2 High Gain Specular Screens 12.3 A Light-Reflecting Electromagnetic 12.4 7000 Lumen Color TV Projector 12.5 Optimum Photoconductor A. I. LAKÁTOS, W. H. COOK AND 12.6 Read-Out Considerations for a G. DIR, J. ADAMS, W. HAAS AND J.

Page 18 / SID Journal

Bioluminescence-Light Without Heat Chancellor, University of California San Diego, Cal. 22 San Diego Room

### 11.3 DC Gas Discharge Storage

G. W. DICK Bell Telephone Laboratories, Inc. Holmdel, N.J. 07733

# MORNING 9:00 am - 12:10 pm

# THURSDAY

23 San Diego Room

AFTERNOON 1:00 pm - 3:00 pm Session 13 **DISPLAY APPLICATIONS** L. N. HEYNICK Stanford Research Institute Menlo Park, Cal. 13.1 On-Board Vehicle Route Instructions Via Plasma Display Panel R. L. FRENCH Avcon, Inc. Ft. Worth, Tex.

13.2 Pilot Warning/Collision Avoidance Display System W. E. BUCHANAN AND E. F. KILEY Johns Hopkins University Silver Spring, Md. **13.3 Naval Environmental Display** Station (NEDS) W. O. KERMAN AND E. R. REINS U.S. Navy Environmental Prediction **Research Facility** NPS Monterey, Cal. 13.4 The Epic-II System for

**Experimental Electronic Painting** V. J. FOWLER GTE Laboratories Inc. Waltham, Mass.

# THURSDAY

23 Golden West Room

AFTERNOON 1:00 pm - 3:00 pm Session 14 INTERACTIVE SYSTEMS Chairman T. B. CHEEK Tektronix, Inc. Beaverton, Ore. 14.1 Knowledge Workshop Terminal Systems R. W. WATSON Stanford Research Institute Menlo Park, Cal. 14.2 Systems Aspects of Displays D. E. LIDDLE Xerox Research Center Palo Alto, Cal. 14.3 Image Storage and Retrieval L. Hausman Infodetics Corp. Anaheim, Cal. 14.4 Micrographics/Computer Information Display System R. L. MERWIN Dynamic Information Systems, Inc. Lakeville, Minn.

# FRIDAY

24 Senate-Committee Rooms

ALL DAY 9:00 am - 4:30 pm SID UNIVERSITY OF CALIFORNIA SEMINAR



It has been suggested (with an assist from adherents to the cult of 'newness') that the cathode ray tube is on its way out. The author points out that despite various new technologies, the CRT survives, and continues to find new areas of application. One reason for this is that few applications have fully exploited its capabilities.

have been taken over by new

technologies. But the CRT contin-

ues to survive and find new areas

of application. Part of the reason

for this is that very few applica-

tions have fully exploited the capa-

By JIM E. WURTZ Senior Applications Engineer Litton Industries San Carlos, California

exaggerated.

Circuit board produced by a cathode ray tube artwork generator.



■ The cathode ray tube is a very bilities of this device. The CRT mature electronic device. Lately, a provides a virtually inertialess combination of the cult of "newpoint of light controllable in brightness" plus emerging technologies ness over a great range with the such as LED's, plasma displays capability of fully random placeand the laser have led many to ment anywhere in a two-dimenpredict that the CRT is on its way sional plane. Neither the data out. To paraphrase Mark Twain, source nor the order of informawhen his name accidentally aption arrangement is important. It peared in the obituary column, has sufficient memory for smooth reports of its death are greatly presentation of data, but is capable of instantaneous change. Certainly many areas of display

While there have been no major breakthroughs in recent years, slow and steady improvement in CRT technology continues. Today a number of new phosphors are available, cathodes are better, assembly techniques are better, and

5", photo recording cathode ray tube producing a 13 micron spot size. with greater cleanliness, tube life

is longer. But it has been the spectacular progress in semiconductor technology that has made it possible to more fully utilize the "power" of the CRT.

The impact of solid state on CRT's is twofold. Because solid state memories, microprocessors, and information handling circuitry have become smaller, better and cheaper, the data to be displayed is available at higher rates. More importantly, the circuits and components for driving the tube itself have become smaller, faster, more stable, cheaper, and more efficient. Deflection amplifiers, high voltage supplies, video drivers, and shaping circuits have shrunk from vacuum tubes to discretes and then to IC's. An example of one area of progress in drive circuitry are the cathode ray tube plotters now in operation which have sufficient accuracy and stability to generate circuit board artwork, interconnect patterns for large scale integrated circuits, and even diffusion masks.

Progress in the areas of drive circuitry and information processing devices continues, along with the growth of requirements for information display devices. Because of these factors, the CRT has only begun to realize its full potential in the last few years. Aside from the great proliferation of computer display terminals and oscilloscopes, there follows a partial list of applications where the CRT is the workhorse. Most of the listed applications are film

oriented. Satellite imagery ATS ERTS

TIROS

NIMBUS Mariner, etc. Forest fire detection and mapping (IR readout) Seismic section recording Well logging Biomedical

Ultrasonagraphs Cell counting Image analysis



Automatic nuclear particle scanning

Computer on microfilm recording Magnetic tape to film recording Graphic displays Mask and circuit board generation Radar land mass simulators Simulator scene generators Side looking radar recording Document reading (OCR) Color picture "camera" Computer image research Helmet-mounted displays Photorectification (aerial survey) Facsimile Electronic phototypesetting Photo color separations Sonar recording High speed oscillography Large screen displays Many of these applications can

be done no other way than with the CRT, especially in cases where random scanning or nonlinear spot motion is required.

Of great interest right now is image processing for earth resources, computer on microfilm,



### 9", line scan fiber optic cathode ray tube for dry process film recording.

and electronic phototypesetting. Many other new applications have opened up with the emergence of more sensitive quick process films such as 3M brand dry silver which allows almost instant access to the image without chemicals. The availability of good quality fiber optic faceplates for cathode ray tubes has reduced recording system size while increasing the performance level in many applications.

As previously noted there have been some advances in CRT technology. New rare earth phosphors which are a fallout from research into improved materials for entertainment TV have made possible excellent color recording and high contrast cockpit displays. Brightnesses of over 15,000 foot-lamberts have been reported for tubes used in large screen projection displays.

The current practical state of the art in spot size is about 13 microns. The word practical is used advisedly here in that it is possible to order and receive a CRT from a

tube manufacturer which will ex- many improvements in precision hibit this spot size when measured in a scientific fashion. It is appropriate to note that although there are still some weak areas (particularly in brightness specifications), measuring and evaluating CRT's part to solid state technology.

tions encountered in electron beam control and lens losses, it is possible to order a CRT system which will record a 4000 x 4000 element picture where the picture element structure can still be seen. Photographic-like quality is achieved by the use of redundant element position digital-to-analog converters of 8000 positions or more. For a single line type display close to 8000 elespeed versus resolution.

years, although there have been

of assembly and cathode materials. The only new gun technology of note is the development of multibeam guns announced by Sylvania a few years ago. Although Sylvania chose to withdraw from the indushave also improved, again due in trial and military CRT business (as did GE and Rauland), others Teamed with normal degrada- have picked up the technology. Currently, the single gun multibeam CRT is being used for multielement infrared display with up to 20 beams of less than 25 microns each in size swept together, but individually modulated. There is, of course, further potential for this device in high speed alphanumeric character generation.

Perhaps some day it will be possible to electronically deflect the ments can be demonstrated where laser in a practical manner, or the element structure can still be LED's can be packed closely seen. All of the above figures have enough and with enough brightthe usual tradeoff of brightness or ness to be useful and practical. In the meantime, the ubiquitous CRT Electron gun design has not continues to achieve its true deschanged significantly over the tiny with the help of the exploding field of solid state technology.



on this Timely Topic.



# **Thomas Electronics** your best source for all commercial, industrial, and military applications

Large modern production plant ... fully equipped R&D laboratories ... outstanding production, engineering and applications personnel ... integrated support both for short-term and long-term programs ... professional owner-managed, independent company ... write or call ... we promise fast reaction to your inquiry ... Our NEW Short Form Catalog is available upon request.



COMPUTER DISPLAY CONSOLES CHARACTER READERS & FILM SCANNERS DESK TOP CALCULATORS HEAD-UP, RADAR AND OTHER AVIONICS DISPLAYS FOR SEVERE ENVIRONMENTS RESERVATION COUNTER TERMINALS HIGH RESOLUTION PHOTORECORDING AND PHOTOCOMPOSITION SYSTEMS MEDICAL ELECTRONICS MONITORS PROJECTION AND SIMULATION SYSTEMS OSCILLOSCOPES & STUDIO EQUIPMENT AIR TRAFFIC CONTROL AND GROUND SUPPORT DISPLAYS

# 1AS ELECTRONICS, INC.

100 RIVERVIEW DRIVE, WAYNE, N. J. 07470 / Telephone: 201 - 696-5200 / TWX: 710-988-5836 / Cable: TOMTRONICS

# **CHALLENGE:** Select a display for today,



Totalscope II displays. Lightweight subsystems in a single package. Ask about: internal processing, low-cost growth to multi-function, plasma displays, high MTBF, lower logistic support costs, 4000 flicker-free characters, off-the-shelf availability including computer interfaces.. and a lot more.

You're looking ahead...and looking worried. Military display needs keep getting more complex and there's still more sophistication looming on the horizon like a fast moving thundercloud.

And your budget is tighter than ever.

It seems like a rotten choice; you can solve immediate problems within your budget by selecting a system that will be obsolete by the time it's uncrated or you can get one with psychedelic lights, guaranteed to glow in the dark. It'll look nice...as its inflexibility forces it to become obsolete.

The Motorola solution to your dilemma:

Totalscope II, the off-the-shelf random position display that lets you pay for just what you need now. Without hurting your future because Totalscope's design utilizes time multiplexing and bus organization to allow additions whenever you wish.

# So good our competitors recommend it to their customers.

Some of the biggest display manufacturers in the country-people we often bid against-have at one

time or another recommended Totalscope II. You know what that's like for a salesman? But they did it even though they had a choice,

just like you have a choice.

One of the reasons is that Totalscope II gives more choices than any other fully militarized display in existence. You pick the controls. You pick where they go. You choose the options you want.



Works-in-a-drawer Totalscope II is modular all the way through ...from plug-in functions, to CRT shape and size, to where you want the control knobs.

# tomorrow, and the 1980's.

And even if you pick them all, you won't end up with a monster. Nor run up an outrageous price.

# Reliability means 125 days and 125 nights.

The MTBF on Totalscope II, following MIL STD 756, is over 3,000 hours. That's 125 days of 24-hour operation. Self-test for hardware and software plus a BITE diagnostic module are immediately available. And since Totalscope II is far more than just a slave display, it can stay up when all else is going wrong. An optional keyboard lets you overlay real time sensor data with operator generated material. The light pen module lets you call out specific data on the spot. And all this won't get in the way of information flow because the unit's specific modules let you see hardware instead of wasting memory space and computer time with software.

# Pick a card, any card.

Alphanumerics? We'll give you 4,000 flicker-free characters. Our engineers say it's the fastest response of any non-raster system. And since Totalscope isn't a raster system (unless you order a raster card) problems with the host computer compiler can't mess up every



To add capability, change functions, or quickly troubleshoot your Totalscope II, just plug in a module.

display in the house. Totalscope II can automatically refresh itself so one team can keep solving real time problems while another one tries to exterminate the bug.

Want to add graphics too? Just plug in a graphics module and appropriate memory.

You'll find similar simplicity with other cards that supply up to 127 radii offset in any direction, magnification of character/vector positions and vector length. Ditto for cursors and tags, an editor, a display buffer module, readout module, and even a module for drawing fine detail maps or geometrical patterns. Four color capability gets a bit more expensive.

# How selecting options saves money.

If Totalscope II sounds expensive, remember that almost everything is an option, so you only have to get fancy when fancy is needed. And since you only buy what you need you save the weight of useless-to-you



Totalscope II's bus organization avoids problems by treating internal options as if they were peripherals.

features. Weight is typically just 110 pounds. If you select a rack mount instead of a case, you can even save an extra 10 pounds.

People keep on selecting Totalscope. Because they face the problem you face; solving display problems for right now and the long run.

Enough. For a list of impressive statistics and programs for which the unit was purchased, drop a line to: Display Systems, Motorola Government Electronics Division, 8201 E. McDowell Rd., Scottsdale, Az. 85257. While you're at it, tell us your problem, or call William McCreary at (602) 949-3256. Outside the U.S.A. call any of our offices in Toronto, Paris, London, Bonn, Geneva, Amsterdam or Rome. Then you'll know all the reasons why our competitors recommend us. And exactly how little it costs to have Totalscope II help you meet the challenge of today, tomorrow, and the late 1980's.



... new thinking in electronics

Circle #11 on Readers Service Card

# **Social Implications**

Research in identifying a "natural" display language

• Over the past quarter century or more, considerable emphasis and development effort have been expended to better define, and improve the so-called Man/Machine relationship, that unique interface through which man with his superior intellect has been able to communicate with, and to control his exanimate, but more versatile and powerful partner to successfully achieve functional cooperation. Now, a new dimension has been added to that complex equationnamely a highly successful and demonstrable, three-way Animal/ Man/Machine interface.

In what must be considered an amazing breakthrough in both psycholinguistic and primate research. a team working at Emory University's Yerkes Primate Research Center in Atlanta, has combined a three year old female chimpanzee named Lana, a PDP-8E computer, IEE projection readout displays and a composite graphic language to conclusively demonstrate this simian's ability to effectively communicate via a new and unique visual technique. The team is headed by Dr. Duane M. Rumbaugh, Chairman of the Psychology Department at Georgia State University and is conducting its research under grants from both the National Institute of Child Health & Human Development; and The Animal Resources



Lana at the keyboard

Health.

During the past year of study, Lana has acquired a vocabulary of more than fifty nouns, verbs and articles which she retains and readily recognizes. Although sentence English, she has learned to use these words properly to construct and punctuate syntactically-correct sentences and requests which she utilizes consistently throughout the day to communicate and to make her wants known, even when alone in the wee morning hours. In marked contrast with previous studies in animal response such as Pavlov's findings with dogs and their predictable and repeatable reactions, Lana is clearly able to discriminate among objects and actions, and to unilaterally express herself correctly and spontaneously, often without resort to rote or any programmed response, regardless of whether she is interrogated or simply wishes to express a desire of her own.

# Symbols vs. Vocal Cords

Because of vocal chord limitations which make it impossible for primates to emulate the modulation and tonal variety necessary for human speech, the researchers decided to adopt a visual technique utilizing discrete graphic symbols for specific objects and actions. Known as "Yerkish" and developed by Professor Ernst von Glaserfeld, a psycholinguist from the University of Georgia, the language at the base level consists of nine symbols

Branch of the National Institute of or single design elements (Figure 1). Through simultaneous projection which precisely superimposes two or more of these basic elements on the same screen, composite symbols called lexigrams are created. Unlike English or other human construction differs somewhat from languages, each composite has only one specific meaning in order to avoid ambiguity, and to preclude confusing Lana. Three basic color backgrounds (yielding seven discrete, composite colors) are also used to assist in discrimination.

In developing Yerkish, Professor von Glaserfeld has utilized a conceptual and correlational approach to the relationship of word classes which differs from conventional "subject-verb" type of sentence construction. Instead, Yerkish relies more on an "actor-activity" method of expression with additional words serving as correlators, objects of an action, and as punctuators. Accordingly, Lana is able to construct meaningful sentences or expressions which, though they may sound somewhat grammatically stilted in English, are conceptually correct. On the other hand, the computer logic is so programmed that if she constructs an expression which, though syntactically correct in Yerkish, is functionally wrong, the computer rejects her input out of hand. Samples of Lana's Yerkish lexigrams are shown at Figure 2. As mentioned above, the nucleus



(above)

of the Emory University system is PDP-8E computer; and 14 each of Industrial Electronic Engineers' (IEE) Series 360 and Series 10 Rear Projection Displays. A modular, vertical keyboard panel of five banks of 25 keys each in a 5 x 5 matrix (until recently only three of the five were in use), and the associated interfact-logic, electronics and software were designed and developed at the Yerkes Center under the direction of Professor Harold Warner, a biomedical instrumentation systems specialist, and his associates.

# Arrangement of Displays

The Series 360 displays with their 2" characters are arranged in two banks of 7 projectors each, one above the other directly over Lana's keyboard with the lower set directly connected to the output of her keyboard through the computer, and the upper set slaved to the output from an experimenter's console outside Lana's enclosure. The smaller Series 10 displays are located in similar but inverse fashion at the experimenter's station where they simultaneously display the messages which Lana composes, as well as information the researcher may wish to display on the upper bank of Lana's projectors. In this interrelated fashion, each input resulting from Lana's depression of a single lexigram key is fed into the computer and then simultaneously displayed on one of the feedback projectors inside the enclosure and at the researcher's station outside the chamber. Depression of any one of the keys at either keyboard activates the com-

Mar.-April '74 / Page 27

puter memory which selects the correct elements of the corresponding lexigram in the computer's dictionary and transfers the composite representation to an internal parser, while at the same time transmitting the appropriately binary coded signal representing the basic elements of that particular word to an external decoder which drives the projection lamps of one of the 7 lower projectors, thus displaying the reconstructed lexigram on the face of its screen. The interface logic is such that the corresponding lexigram for the first key depressed is projected on the first display, and succeeding words are displayed on the other projectors from left to right in incremental step fashion.

In order to activate the system, Lana must first pull down or hang from an overhead bar above the recorded printout of all events keyboard. Having activated the which transpire including the time system, she may then proceed to enter her request in proper sequen- rect sentences, nature of errors, retial fashion and in a format that is starts, and ultimate results. In this conceptually correct. Finally she manner, experimenters have been

pletion. Should her message be a request and she fails to preface it with the "please" symbol, or should she insert a lexigram which is conceptually incorrect such as "PLEASE MACHINE GIVE WIN-DOW" (rather than with the symbol "OPEN WINDOW"), or should she fail to terminate with the period symbol, a buzzer sounds, the feedback projectors go blank, and she must start over. Conversely, if the sentence has been both procedurally and conceptually composed in correct fashion, a bell sounds to signal its correctness and the computer activates the appropriate action or reward such as opening the window or dispensing food. The computer is also programmed to maintain a continuous and nature of all messages, incormust terminate each sentence with able to monitor Lana's activities

the period symbol to signify com- while she is alone during early morning hours, and have learned that she will frequently request music, activate the movie projector in order to entertain herself with the "late, late show", or open the window at davlight in order to watch early morning traffic outside the building. They have also been able to determine her distinct preferences for various types of music (jazz is her favorite) and foods such as M&M candies (for which she has developed a particular fondness).

> The team of researchers has been delighted with Lana's rapid progress and her ability to readily learn and discriminate such a wide variety of objects and activities. To preclude any possibility of automatic reflex or positionally-related response, the physical positioning of the lexigram keys is frequently changed in random fashion, yet she invariably is able to locate and select the correct lexigram to express herself. Moreover she has shown additional aptitude to cor-



Circle #12 on Readers Service Card

NEVV! PHOTOCHROMIC **RECORDING PAPER "ISSEC"** ISSEC Laboratories have developed a new photo-sensitive surface able to record without processing a high resolution image (photograph, diagram, text) with the possibility to erase this image and reuse the sensitive surface for a new recording, a great number of times, without altering the quality of the recorded image. The number of recording-erasing cycles can reach several hundred The image can be completely or partially erased thus allowing

to add or subtract at will parts of the image (photocomposition). The recording on the paper can be reproduced by any of the standard photocopiers to provide a permanent record.

Some of the many uses of this paper are listed below:

- Computer data processing.
- Laser recording.
- Hard copy from cathode ray tube displays.
- Temporary recording of UV galvanometer trace.
- Evaluation of positive pictures from a nega-• tive.
- Event recording.
- Monitoring, medical and technical.
- Photocomposition, etc.

The photochromic recording paper is sold in boxes of 100 sheets 9 x 12 cm. Other dimensions are available upon request. For information write to:

> ISSEC 4, chemin des Fleurs

01210 FERNEY-VOLTAIRE

FRANCE

Circle #13 on Readers Service Card

rectly complete partial sentences constructed by the researcher, and to detect conceptually incorrect sentences displayed to her. In the latter case, she has signaled her detection of the error by hitting the erasure button in over 90% of the time, and similarly when she errs in constructing her own sentences, she invariably catches her mistake and corrects it.

While overjoyed at Lana's progress, team members are reluctant to predict the ultimate results of such experimentation. Admittedly years ahead of schedule after only one year of work, delighted team members are theorizing that they may possibly progress to a point where direct interactive conversation between animal and researcher may be possible, or even in a more advanced concept, primate to primate conversation may ultimately be achieved.

The IEE's Series 10 and 360 Rear Projection Displays currently being used are both standard catalog items, each projector being capable of displaying one or more of 12 discrete messages stored on a film chip. The 360, which weighs less than 1½ pounds, is 7.8" x 2" x 4" overall and displays a 2" character, viewable at 40' through 160° with 40 F/L brightness at 6.3 VDC; the venerable Series 10, the first successful rear projection display ever demonstrated, weighs but 12 ounces, measures 11/2" x 21/2" x 51/2" and projects a .94" character, visible at 20' through 160° with 75 F/L brightness at 6.3 VDC. Both units utilize a 3 x 4 array of 12 lamps (6.3, 14 or 28 VDC) and a unique, patented light collecting lens and projection system with a radially curved, mylar film chip to project alphanumerics, whole messages, symbols, graphics, colors, or anything else photographically reproducible, essentially distortionfree on a non-glare, ground glass screen. While the many diverse applications for which these versatile units have been utilized are far too numerous to recount herein, their novel adaption to primate communication must rank as one of the most unique and unanticipated uses ever.

Aside from furthering man's knowledge and a better under-

standing of primates' linguistic potential and learning capacity, Dr. Rumbaugh and his team's investigative efforts may contain corollary, and perhaps more far-reaching implications, namely that the insight gained therein, into concept formulation and language acquisition may prove invaluable in the evolution of meaningful programs for the intellectual development of retarded children, and other handicapped individuals. The positive application of information display



The HIGH ACCURACY SPECTRA® 1980 is totally free of polarization error, and is sensitive down to 10-5 foot lamberts full-scale.

The VERSATILE SPECTRA® 1980 functions as either a microphotometer or telephotometer - measuring luminance, illuminance, radiance, color temperature, tristimulus color, etc. - from 0.001 inches to infinity. Five easily selectable measuring fields provide angular coverage from 2 arc-minutes to 3.2 degrees.



technology in ursuit of such a goal can only be most gratifying to all of us.

# **Optical Diodes' LED**

Optical Diodes, LED maker set up recently with backing of Stanlev Electric Co. of Japan, is moving into watch modules, opto isolators and 14-digit displays for scientific calculators at a plant in Palo Alto, California.

# Set your sights on a Spectra<sup>®</sup> 1980 Pritchard<sup>®</sup> Photometer

SPECTRA® 1980 - the only precision photometer with Auto-Comp™ which permits AUTOMATIC readout of light in DIRECT UNITS, regardless of filter, aperture or range setting selected.

# PHOTO RESEARCH The light measurement people

3000 No. Hollywood Way, Burbank, California 91505 (213) 849-6017 • Telex 66-2429 A Division of KOLLMORGEN Corporation

Circle #14 on Readers Service Card



AULTICOLOR &

Color coding improves recognition and response time. However, most CRTs show only black-andwhite pictures. Most color CRT development has been for color TV, rather than scientific or industrial applications. The penetration color tube is designed to rectify this.

> Thomson-CSF Grenoble, France

# By ANDRE MARTIN **Why Multicolor or Multipersis**tence Displays?

The use of color for visual information is an unquestionable improvement since it enables one to display more and more complex information while maintaining an excellent discrimination of its contents. Studies about human factors have shown that color coding improves the accuracy of recognition and reduces the response time.

Thus it is surprising to consider that most cathode ray tubes designed for scientific or industrial applications show only black-andwhite pictures. If we consider that a professional display must be looked at with close attention in order to recognize without hesitation the different parameters of the display and if we think that the retinal zone where the eye automatically focuses images when it peers at something is composed only of color sensitive cells, it seems absolutely abnormal to misuse the eye to such a point with monochrome displays.

The reason for the lag is that most color CRT development work to date has been for color television and the characteristics of a good color T.V. CRT such as a shadowmask tube or Trinitron do not fit the requirements for a good information display tube.

A relatively new class of device, the penetration color tube, has now been developed to the point where it fulfills those requirements (high resolution, color uniformity and picture brightness).

# Penetration C.R.T.

# Operating principle: how does penetration CRT work?

The CRT has a multilayer screen consisting of two phosphors of different colors separated by a layer of transparent dielectric material (fig. 1). The two phosphors produce different colors when excited by an electron beam. A beam of too low a voltage to penetrate the dielectric barrier layer will excite only one phosphor. Higher voltage will excite both phosphors with



### Figure 1. Color penetration tube principle.

predominance of the second phosphor color. Intermediate colors will be obtained from intermediate voltages. Several colors can then be produced by a single electron gun by simply switching the acceleration voltage.

For example, if the phosphor layers produce red and green light when excited individually, the tube can be made to produce four distinct colors: red, orange, yellow and green.

As the acceleration voltage is switched from one value to another to produce the different colors, the current through the magnetic deflection yoke must be adjusted to keep the magnetic deflection amplitude constant and the beam current must be modulated to keep the picture brightness constant.

# For color, displays choice of basic colors

Besides the ability to display large amounts of meaningful information, the color characteristics of

the penetration tube enable an operator to use it for long periods of time with minimum eve fatigue. Some of the reasons for this adaptability are related directly to the physiology of the human eye. When an observer wants to watch closely a display, without being rapidly tired, this display must contain only small amounts of the blue colors. Clearly, the best basic colors to use for accurate observation are green and red with their hues chosen to correspond exactly with the peaks of the spectral absorption curves of the cone pigments. By mixing red and green colors in the proper amounts, orange and yellow can be produced. These colors are not sufficient to reproduce all of the colors encountered in nature and therefore required for a home color T.V., but they are adequate for information displays where colors are used to code a great number of symbols, sketches, figures and so on and to give better recognition accuracy.

# For multipurpose displays, choice of color and persistence

Many other types of phosphors may be used to make other penetration CRT's for a wide variety of applications. For example: red-towhite screen, monocolor or multicolor displays with variable persistence screen, adjustable antiflicker screen. These are described following.

# Main characteristics of penetration CRT

The penetration CRT is characterized by the absence of any internal mechanical device for the separation of colors and by its need for only one electron gun. Despite its simple construction the penetration CRT is the only one which allows the manufacture of bright, high resolution displays required for scientific or industrial graphics applications. Its main characteristics, therefore, are:

-good resolution, over 1500 T.V. lines.

### By ANDRE MARTIN

- -high brightness in the high voltage mode, good brightness in the low voltage mode.
- -no convergence circuitry need to superimpose the elements of a picture (uses only one electron gun),
- -deflection angle not limited by the color separation device since it is built into the screen.

In addition to the four preceding characteristics, the penetration tube has a quality that sometimes is an advantage and at other times is a disadvantage. This is the impossibility of producing more than one color at one time. Because it is a single-gun device, the penetration tube can only select colors in a sequential mode; the appearance of a simultaneous selection is accomplished by the persistence of the eye. The consoles must be constructed in order to take advantage of this property.

# **Different Types of Penetration Screens**

Red-to-green screen

The console manufacturers need tubes having the following characteristics:

- -the smallest voltage swing,
- -very good color uniformity in intermediate colors, for instance orange and yellow, on the whole screen area.
- -maximum color separation and brightness.

For instance, line brightness of 2500  $cd/m^2$  in the red color at 610 nm can now be achieved. Two years ago, such a level was unthinkable. Corresponding line brightness of 7500 cd/m<sup>2</sup> in green color (550 nm) makes possible THOMSON-CSF special penetration CRT to be used in airborne equipment, in fast writing speed display consoles, and so on.

To achieve these requirements, R & D has developed two new types of screens:

Screen E 20 (fig. 2) works at low voltages, from 7,5 kV for deep red (at 610 nm) to 12,5 kV for pure green (at 550 nm). Great care has been taken to obtain the best scale of colors, with the lowest voltage steps. As an example, four distinct



Figure 2. Characteristics of screen E20.



Figure 3. Characteristics of screen E21.



Figure 4. Variable persistence screen characteristics.

# SELE-SCAN PANEL portability

When designing portable terminals . . . for the salesman, auditor, engineer, or anyone who must question his home office computer and get back immediate answers displayed in large, bright, legible characters ... use the Burroughs Alphanumeric Panel Display.

SELF-SCAN Displays are truly portable ----Models are available to display:

- 1 or 8 lines of text
- 16 or 32 characters per line
- Full messages up to 256 characters
- Alphanumeric or numeric readout

Ideal for field access to home-office computer . . . and it is available today . . . at low cost.

For complete information call or write Burroughs Corporation, Electronic Components Division, P.O. Box 1226, Plainfield, N.J. 07061, (201) 757-3400.

A Burroughs sales engineer will show you why a Self-Scan Panel Display is . . .

# your best connection to the home office computer











Circle #15 on Readers Service Card

# POLACOAT

# REAR PROJECTION SCREENS



GLASS

Durable • Maximum Scratch resistance and stability • Easy to Clean

# ACRYLIC

Light weight • Break-resistant • Easy to Clean

# COMPLETE FABRICATION SERVICE

Silk screening • Holes • Slots Notches • Circles, etc. • Ready to Install

# "THE COMPLETE PACKAGE"

- · Consistent high quality
- Choice of colors and finishes
- Technical assistance
- · Prototypes

"Quality Products for Imagery and Light Control — Since 1946"

# POLACOAT, Inc. 9750 CONKLIN RD. CINCINNATI, OHIO 45242

Circle #16 on Readers Service Card

# By ANDRE MARTIN

colors, red, orange, yellow and green can be obtained from 8,5 kV —red, 9,2 kV—orange, 10 kV yellow, 11,5 kV—green, the total voltage swing being 3 kV. This screen, E 20, is recommended for tube sizes up to 9 inches screen diameter when used under heavy ambient illumination and up to 16 inches screen diameter when used in normal ambient illumination conditions.

When display consoles must be used under very high ambient illumination, or when the screen area is exceptionally large, for instance 22" radar CRT, with limited screen current density, screen E 21 can work from 10 kV for deep red to 16-17 kV in green (fig. 3). More screens are under development and intended for airborne displays, where ambient illumination up to 70,000 lux (\*) can be experienced. Measurements with photometers have corroborated visual observations, and screen brightness has reached such levels which could not have been previously foreseen.

# Red-to-white screen

This type of tube can produce ordinary monochrome T.V. pictures and the red color is used to underline or encircle areas of particular interest. Brightness and resolution are equivalent to a conventional black-and-white tube with in addition the red color ability.

# Variable persistence and antiflicker screens

The dream of every radar manufacturer and user has always been a variable persistence tube that would allow the display of lowrepetition rate information such as radar video on a long persistence screen, and, at the same time, allow the display of such rapidly moving information as labels and position symbols on a short-persistence screen.

For small size cockpit radar displays, the direct view storage tube has provided a realization of that aim. But until now, no solution has been available for larger dis-

\*( $\pm$ ) 1 lux=1 lumen m<sup>-2</sup>=0,1 fc dles over 7 million passengers.

Activation of the owner

plays of more than 10" diameter. Variable persistence screens can provide a solution for such displays. In such applications as LLLTV

or Radiological TV, signal fluctuation can severely limit the amount of information that the operator can glean from the display. A longpersistence phosphor can effectively integrate the signal, thus reducing the noise, but it can also cause smearing of the picture. A penetration CRT combining a mediumpersistence phosphor with an antiflicker phosphor of the same color provides a partial solution to this dilemma. Manual selection of the CRT's screen operating voltage allows the operator to make the optimum trade off between noise reduction and smearing for each individual situation.

Fig. 4 shows the decay variation to 10% of initial brightness for different high voltages of a variable persistence screen.

# Display Complex For Dutch Airport

N. V. Luchthaven Schiphol has awarded a \$1.2 million contract to Conrac Corporation for installation of a comprehensive Flight Information Display System during Phase I of the airport's seven-year, three-phase expansion program.

The contract includes design and installation of a complete control system for presently existing flight information boards and extensive new equipment. Four new video controllers will provide 72 channels of video to more than 170 Conrac CRT monitors. In addition 59 splitflap display boards will be installed, ranging from four large arrival and departure hall boards through smaller single line, three line and eight line boards at pier entrances, exit gates, custom halls and baggage areas.

An interesting feature of the Schiphol design is the "gate-dedicated" video provision. In addition to the information on imminent departures displayed to the public on split-flap boards, each gate will have its own video channel that will show operations personnel future departures and gate change information.

Schiphol Airport presently hanles over 7 million passengers.



By ROBERT M. LEE Lawrence Laboratory Livermore, California

The author suggests users of computer graphics displays not rely entirely upon tests provided by the manufacturer; and provides test patterns designed to evaluate specific characteristics.

• In evaluating computer graphic displays don't rely entirely upon demonstrations and tests provided by the manufacturer. Be prepared with two kinds of tests of your own: test patterns designed to test specific characteristics of the display and pictures representative of the work you intend to do on the display.

The four test patterns to be described here wer written to test specific characteristics of a vector diplay, a Control Data Corporation DD80C, which i used in conjunction with a 35mm motion pictur camera to produce pictures ranging from simpl graphs to animated movies. These test patterns hav also proved useful in testing storage tube display and raster displays.

# Hum Test

The test pattern shown in Figure 1, Hum Test detects the effect of stray magnetic fields on th positioning accuracy of the display. A cathode ratube is very sensitive to such fields that are provided in abundance by transformers and chokes.

The principle used in this test pattern is to write a cross on the screen and then, some time later,

# FUNCTION OF THE STREET OF THE

iy																
ŊУ	8	8							88	8	œ					
ts	8	8	8		8	6	8	8	88		88	8	B			8
ic																
a-		8	8	68	æ	8	8	8	18	8	æ	8	B		æ	•
y.	8	æ	8		8	œ	8	8	8	•	8		₿	8		æ
re		8	8	8	8	8	0	8	60		88	8	8	æ	8	
s-		8			8		m		m		-					
is		190		-77	-	-	-			-	-	-				-
re		8		8	8		6	8	88	8	8	8	8	8	8	8
le	8	8	8	8	۲	æ	8		81	8	8		8		8	
<i>v</i> e	8	8		8	8	8	8	8	65	8	8	8	8	8	5	
ys		8	8		8		8		8	8	8		8		8	a
		B	8	æ	8	B	æ	8	8	8	8	₽	8	₿		8
		Ð	6	8	8			8	88		8		8	8	8	8
it,		8	8	8	8	8	œ	8	8	8	8	8	œ	₿	8	8
iy		8	8	B		•	₿	۵	8		⊞		œ	8	8	8
d	8	តា	8		6	8	æ	8	Ø	8	⊞	₿			8	₿
te	₿	8	۵		8	8	0	8	Ø	в	æ	8	8		⊞	Ħ
r,						Fi	aure	1.	Hur	n Te	est.					

# ADD YOUR OWN APPLICATION FOR OUR NEW MINIATURE CRT'S.

- Helmet Mounted Displays
- Compact Video Recording
- Data Annotation
- Visually Coupled Systems
- Remotely Piloted Vehicles
- Head-up Displays

Whatever your application, our new miniature 1" through 2" CRT's will meet your requirements. Typical specifications: 100 ft-lamberts brightness and .001" spot size (better resolution and brightness available on specific models). Tubes are available with plain or fiber optic faceplate, packaged with a deflection coil and fully potted in a magnetic shield. Litton miniature CRT's are produced with the same expertise and attention to quality that characterize our entire high resolution line. Electron Tube Division, 960 Industrial Road, San Carlos, California 94070. Telephone: (415) 591-8411.

ELECTRON TUBE DIVISION



Circle #17 on Readers Service Card

attempt to write a square surrounding the cross. If they fit exactly, all is well and good; if not, you have detected a positioning error.

The complete test pattern is written by first drawing crosses (like plus signs) starting at the lower left corner of the display and going across. When the first line of crosses has been drawn, the beam is returned to the left edge of the display and raised to the next line. When the last cross has been drawn, the beam will be in the upper left corner of the display. Immediately start to backtrack, drawing squares around the crosses. The time delay between writing the cross and the square in the upper right hand corner will be a few microseconds on a typical display. The time between writing the cross and the square in the lower left hand corner can be as long as desired, depending upon the number of squares and crosses and the speed of the display. In some cases it may be desirable to artificially lengthen the total time by programming delays between the symbols.

Any change in the beam positioning during the writing of the test pattern will show up as a misalignment of one or more cross-square pairs. Furthermore the direction and magnitude will be shown. In our application we used squares, ten display divisions on a side, and crosses, with arms ten display divisions long. This makes it easy to estimate numerical values for the magnitudes of positioning errors. In a high resolution display, with high positioning accuracy, it might be desirable to use smaller symbols.

If you are looking for the effect of a.c. fields on the display, a time of 17 milliseconds (one cycle at 60 Hertz) is appropriate for writing the entire test pattern. As might be expected, positioning error will gradually change from maximum to minimum values as the test pattern is scanned. We have also seen random positioning errors using this program (only one cross pattern in the field misaligned with its enclosing square) and, to our surprise, we discovered that the camera was sometimes starting to advance the film before the picture had been completed. The time at which the motion of the film started was clearly visible and we could easily have calculated its rate of acceleration had we wished.

This test pattern is also useful as a test of focus over the entire face of the tube because of its small, evenly distributed, symbols.

# **Resolution Test**

As contrasted to the simplicity of the Hum Test, the Resolution Test, shown in Figure 2, is very complex. It provides a quantitative measure of resolution for use in comparing displays with each other. In the course of time other useful features have been added.

The resolution patterns in each of the four corners of the Resolution Test are identical. They are not only useful for comparing one vector display with another, they can also be used to compare the resolution of a vector display with the resolution of a raster display.



Figure 2. Resolution Test.

The triangles are drawn using lines, the squares are drawn using points (dots). The triangles with a "1" are drawn with one line, one space, one line, one space, one line. The adjacent squares are drawn with one point, one space, one point, one space, etc. The



# **Packaged or Plain.**

Try buying your next CRT from us. We have packages containing tube, deflection and focus coils, mounting, mumetal shield and optical interface. That's all you need. And since you're buying Ferranti, it's the best anyway. Packages are only part of our CRT business, which includes a huge range of tubes, from 1 inch to 24 inch airborne tubes, radar tubes, tubes with rear port facilities, high resolution tubes, head up and head down tubes, and many others, solidly engineered for a long reliable life.

Circle #18 on Readers Service Card

# By ROBERT M. LEE

triangles with a "2" are drawn with two lines, two spaces, two lines, two spaces, and two lines. The adjacent squares are composed of clumps of four points (two x two), the clumps being separated by two spaces from the next clump in any direction. The triangles with a "3" are drawn with three lines, three spaces, and so on.

Another resolution test is provided by square waves that are composed, as labeled, of dots and lines. The largest square waves are six picture lines high, the next are five picture lines high, and so on.

In high speed displays, the power required by the deflection circuits can become a problem. We have included in the Resolution Test, a test to see whether the positioning accuracy of the display is affected when the beam is held in one part of the display for a while, and then quickly moved to another part of the display. We have already discussed the 1, 2, 3, and 4 within the triangles. The other numbers in the test show the order in which the parts of the test were written. The small squares at the edges of the test were written first, second, third, and fourth respectively The horizontal lines were written fifth, and the resolution pattern in the upper left corner was written sixth. This complex pattern requires that the beam be deflected in the upper left quadrant for a long time.

Ferranti Electric Inc. East Bethpage Road Plainview, New York 11803 Telephone: 516/293-8383

FERRANTI

VISIT US AT SID'74/BOOTH 102

# By ROBERT M. LEE

immediately after that resolution pattern is completed, the cross is written at the extreme right edge of the test as the seventh symbol to be written. If the deflection circuits have been overheated in drawing the preceding pattern, they are likely to not properly center the cross in the square. If you follow through the rest of the numbers you can see that after each resolution pattern is drawn, a cross is drawn in a reference square. We have tested one display in which this proved to be a serious problem.

The sets of horizontal lines in the center of the screen are used to compare the relative brightness of lines of different lengths. In the DD80C long lines are drawn at higher writing speeds than short lines. This means that if short and long lines are to appear of the same intensity, some compensation must be provided. The horizontal lines show whether the intensity compensation has been adjusted correctly.

A last point. We have labeled this test pattern with its source, name, and the date of its last revision. This is most useful for people in an organization who may may find themselves using a test pattern about which they have questions. The label is included in three of the test patterns described here. It is not included in the first because it might interfere with the interpretation of the results obtained in using the test pattern.

# **Vector Joining Test**

The test pattern shown in Figure 3 was written to test the accuracy with which the display joins lines together. It tests the joining of lines of differing lengths and the joining of lines at various angles.

The central pattern is drawn in one continuous line, starting at the right center. If you trace it, you will see that it starts with a very long line joined, at right angles, to a very short line. The short line in turn joins to a line not quite as long as the first line, and so on. The joints in this pattern are all at the outside edges so that they can be scanned readily. The three herringbone patterns, formed from "v"s whose sides are joined at varying angles, should appear identical, but they are drawn each differently from the other two. In the set at the left of the test pattern, each "v" is drawn in two sequential strokes.

The end of the first stroke is the beginning of the second. In the set at the top of the test pattern each "v" is drawn by a pair of lines, starting from the ends of the "v" and ending at the joint. In the set at the right of the test pattern, each "v" is drawn with the end of the first stroke joining the beginning of the second stroke, as was done in the set at the left of the test pattern. But, after the first stroke is drawn, the beam is turned off and positioned to the center of the screen and then returned to draw the second stroke.

# Straight Test

The test pattern shown in Figure 4 was written to test the accuracy of the circuits used to calculate and draw straight lines between addressable points on the display screen. It also provides a test of the accuracy of the positioning circuits, and will show if there is a difference in line width or brightness as a function of the direction in which the line is drawn.

There are sixteen groups of four lines each. The order and relative direction of drawing the four lines within each group is important and is shown in the inset in Figure 4. The numbers, 1-4, show the starting point of each line and indicate the order in which they are drawn: Start at 1, draw the line, go to 2, draw the line, go to 3, draw the line, and go to 4, draw the line.

If the lines are not straight, this manner of drawing them will cause the curvature to show. If the lines are not parallel, that also will show. The criss-cross pattern at the center of the test pattern is another good test for resolution.

\*Work performed under the auspices of the U.S. Atomic Energy Commission.



Figure 3. Vector Joining Test.



Figure 4. Line Straightness Test.

# **New Comtal Display**

New COMTAL 8000 Series Digital Image Display System is second generation system, will be demonstrated for first time at National Computer Conference, May 6-10, Chicago. It will also be demonstrated at the SID Symposium, May 21-23, San Diego.

Versatile 8000 series will retain all the operating features of the earlier 5000 series (see attached descriptive literature sheet) but will incorporate many new user advantages: (1) Approximately 50% greater real-time processing capability; (2) Greatly increased image display facility; (3) Improved operator interaction, graphic overlay options and target/ trackball options; (4) Field expandable-permits user to start with black and white digital image display and to easily convert system to full color as his applications may dictate. New features expected to substantially expand the applications potential of "true" image processing.

Circle #101 on Readers Service Card

# **Tiny Counter**

World's "smallest digital panel meter," by Non-Linear Systems, Inc., now available in an Event Counter version, the PM-4 (C). An external 3-pole, double-throw switch allows the instrument to function as a computer of up to 9999 pulses from either a DTL or a TTL source, at a maximum rate of 200,000 pulses per second, or as a single range four-digit voltmeter



with full-scale values of  $\pm 1$ ,  $\pm 10$ ,  $\pm 100$  or  $\pm 1000$  VDC. The compact counter/voltmeter is less than one inch high, has "all of the characteristics of the PM-4": high reliability, low power drain (less than 0.5 watts at the standard supply voltage of 5 VDC) and an accuracy of  $\pm 0.02\%$  when used as a voltmeter.

Circle #102 on Readers Service Card

# 35-mm Liquid Gate

optical bench use. Circle #103 on Readers Service Card **Fast Printer** 



The "World's fastest computer peripheral serial printer" is operating in a laboratory in Long Island City, New York. The inventor, Arthur Matschke, co-founder of Tele Speed Communications, has developed an impact printer capable of printing five carbon copies at over 225 characters per second. This dot matrix printer, using a new type of magnetic cell of extremely light weight, has increased the life expectancy of the printing mechanism beyond the known technology. mation has been working on the invention for the last two years. Circle #104 on Readers Service Card



A 35-mm liquid gate is offered by Space Optics Research Labs in its line of precision liquid gate holders. New model consists of 35mm film holder designed for practical insertion into an X-Y micrometer stage which, in turn, provides two degrees of precision, calibrated motion through 1 in. of travel without obscuration to the 2.25 in. clear aperture. The assembly is mounted to an upright for direct application on an optical table or any standard carrier for

# **Power Supply** For CRT Display



Keltron's new Series 800 is a high voltage power supply specifically designed for use in CRT display systems. Up to 4 optional additional plus or minus output voltages can be added with the same line regulation as the high voltage output. Specifications:

Standard Output Voltages (KV): 10 to 20 at 10 watts maximum. Line Plus Load Regulation: 0.1%. Input Power: 115 VAC. Ripple: 0.05% peak to peak. Full Load Transient Response: 0.03% peak recovering in less than 2 milliseconds. Size: 6%" x 4%" x 15/16".

Series 800 features silent operation and the unit is fully protected from damage caused by arcing, overload, a short circuit. With automatic recovery upon removal of Matschke, who holds patents in the fault. Completely enclosed in electronics, fiber optics and auto- an aluminum case. This unit has all silicon semiconductors and is factory repairable.

Circle #105 on Readers Service Card



# Solid State Fetron

Teledyne Semiconductor now has FETRON kits available for solid state conversion of both the HP400 voltmeter and the Tektronix CA oscilloscope plug-in module. These are first of a series of kits designed for replacing vacuum tubes in electronic instruments with solid state FETRONs. The FETRON duplicates vacuum tube performance with a hybrid IFET circuit that plugs directly into the socket. Unlike vacuum tubes, however, the FETRON doesn't drift and doesn't require filament, screen grid or support power, company says.

Circle #106 on Readers Service Card

# LED Mount Hardware



Industrial Electronics Engineers introduce unique universal LED mounting hardware package. Universal panel mount accepts any Dual-Inline LED display packaged with .3" row spacing. Mounting hardware package consists of a one-piece nvlon bezel, a circular polarizing window and a one piece behind-the-panel socket assembly which eliminates all individual DIP sockets. Dual-in-line displays with 14 or 16 pins can be accommodated in presentations from 2 to 8 units.

The one piece socket assembly has wire wrap-terminations that permit economical wiring of any display arrangements.

Circle #107 on Readers Service Card

# **Digit System**



A new, low-cost digitizing system, Model D100, designed for high-speed data reduction applications, has been developed by Broomall Industries, Inc., for accurate digitizing of engineering drawings, circuit layouts, contouring, architectural drawings, and numerical control tape preparation. These and other applications are

performed by the D100 Digitizing System, which measures and automatically records sequentiallynumbered points of X-Y coordinate data on card punch, tele-typewriter, paper tape punch, or on magnetic tape.

"The System has complete formatting flexibility, provided through a unique patchboard system that complements individual computer requirements and allows a variation in word length.

A standard 40 x 60 in. digitizing table is provided with each system. The precision table is adjustable from full horizontal to vertical positions and features power lift for height adjustments.

Circle #108 on Readers Service Card

# James Transformers

Iames Electronics introduces new line of communications and data transformers, featuring high performance cores, providing optimum performance for a wide variety of telephone, communications and data circuits.

Circle #109 on Readers Service Card

# Scanner Can Map

For the first time a scanning electron microscope or microprobe can be used in elemental mapping for simultaneous visualization of element distribution and intensify information in a three-dimensional (isometric) presentation, using new Model 303 Display and Scan Generator, says Princeton Gamma-Tech. It is used in conjunction with a PGT X-Ray Analyzer System and an SEM or microprobe.

Model 303 also provides line analysis and display transfer. In line analysis, the SEM scans a single line while the counts of a selected single element are stored in the multichannel analyzer. Stored data may then be transferred to the CRT display of the SEM to produce a micrograph with the overlaid single line element distribution data and count.



In the display transfer mode an X-ray spectrum in the multichannel analyzer is transferred to the SEM display. This results in the combination of X-ray spectral data and a micrograph of the sample on a single photograph.

Circle #110 on Readers Service Card

# **New Disk Storage**

Itel Corporation's Data Products Group announces new disk storage product, the 7330 Model II disk file, which is capable of storing 200 million bytes of information, or twice the capacity of their present 7330. The new file is said to be a direct, lower-cost replacement for the IBM 3330 Model II file.

Circle #111 on Readers Service Card



**CELCO** makes Precision CRT Displays for your "aboveaverage" CRT requirements.

Need a CRT spot-size as small as 0.00065"? This standard CELCO 5" CRT display is being used for Satellite Photography. They needed the best they could get. You can get performance like that too with CELCO's DS5-065 Precision CRT Display.

A CELCO DS5-08 with 0.1% linearity, and spot size of 0.0008" is being used by another CELCO customer for Nuclear Photography Film **Recording. Special features** include programmable Raster Generators, and triple-layer and articulated shielding for ambient fields from earth's field and from dc to RF fields.

Fingerprint Scanning is the job of CELCO's DS5-10 Optical Character Recognition System for one of our customers. They needed that wide 2.5 MHz deflection bandwidth for highspeed scanning of vast amounts of data. And the DS5-10 has a settling time of

CONSTANTINE ENGINEERING LABORATORIES COMPANY 1150 E. Eighth Street, Upland, CA 91786 70 Constantine Drive, Mahwah, NJ 07430

Our DS5-075 provides NASA with a 0.00075" spot-size for their Viking Orbiter and Viking Lander satellite photography. They needed 0.01% repeatability too. And they got it. From CELCO.

Two different customers with "above-average" display needs are using CELCO CRT **Display Systems for Astronomy** Research. One is an observa-

displays.

Page 40 / SID Journal

10 microseconds to 0.1% large signal, and 350 nanoseconds to 0.02% small signal settling time. Spot-size is 0.001".

One CELCO customer is using our 5" Color Display System for color separation and color photo scanning. One display does all that!

If your needs are "aboveaverage" but your budget is below-average, CELCO also makes a 5" Precision CRT Display System especially for you that's ideal for your Low-Cost Film-Scan applications. Or if your display needs are larger, CELCO makes standard precision 7" and 9" CRT

tory; they're keeping their eye on the Sun. The other is recording their Stellar Observations with a CELCO CRT Display System.

High-speed map making is the task of another CELCO customer using a CELCO precision display for topographical projects.

CELCO displays are helping a leading Oil Company in their oil explorations. While another CELCO display is being used in Eye Research.

Maps and satellites, eyeballs and oilwells. All "aboveaverage" display requirements. If your needs are ABOVE-AVERAGE, you need a CELCO "above-average" Precision CRT Display System.

(Don't you think so too?)

Call CELCO for your "aboveaverage" CRT Display System.

UPLAND CA 714-982-0215 MAHWAH NJ 201-327-1123 (average is so ... ho-hum to us.)



Circle #19 on Readers Service Card



# See what Keltron has to offer.

- LOW COST-UNDER \$40.00 MODERATE OEM QUANTITY
- FIXED OUTPUT VOLTAGE-CHOICE OF 10, 12, 15KV+5%
- LOAD RANGE FROM ZERO TO FIVE WATTS
- REGULATED TO 0.2% OR BETTER
- INPUT + 24VDC, UNREGULATED
- SHORT-CIRCUIT, ARC, AND OVERLOAD PRO-TECTION
- FULL-LOAD TRANSIENT OF 0.5% TO 1% PEAK. RECOVERY IN 3MSEC TYPICALLY.
- SILENT
- OPTIMIZED PERFORMANCE FOR CRT DISPLAY ONE YEAR WARRANT



Circle #20 on Readers Service Card

# **Display Readout**



A 3½-digit data display readout, the AD2015, which can be used as a remote DPM slave display or as a visual readout for a counter. A/D converter, or any other source of BCD data, has been introduced by the Modular Instrumentation Division of Analog Devices, Inc. The AD2015 displays the data on 0.4-inch, bright RCA Numitron<sup>™</sup> readouts, and accepts three digits of standard parallel, positive true BCD data inputs at DTL/TTL logic levels. The digital display module has other inputs to indicate a 1 for 100% overrange, all dashes for overload conditions, and the polarity sign.

The 5V DC power commonly used for logic circuits is all that is required to operate the AD2015. For the logic circuitry in the display, 200mA with  $\pm 5\%$  regulation is required.

Circle #112 on Readers Service Card

# **Xebec Formatter**

Disk-drive formatter that interfaces with all commercially available cartridge disk drives has been announced by Xebec Systems. Designated the XDF-20, the new formatter can be supplied with couplers to match the selected disk drive to most popular minicomputers. Says company: "The XDF-20 offers the OEM or end user a lower cost alternative to the disk systems provided by the mainframe manufacturers. In addition, it offers several important benefits.

Reliability said to be assured through use of a single board which minimizes connector problems and eliminates the need for a fan.

Circle #113 on Readers Service Card

# **Debugging Method**

Binary Systems announces availability of a new program, BREAK-POINT, which allows online interactive symbolic debugging of FOR-TRAN programs at the source code level. BREAKPOINT is an easy to use program that allows interactive debugging of FORTRAN programs. On most small computers, programming in FORTRAN is simple, but the mechanics of compiling, assembling, and creating a load module are complex. Depending upon the computer configuration, it may take anvwhere from 5 minutes with a disc system to 8 hours or longer on a paper tape system to create a FOR-TRAN load module. This load module must be recreated each time a correction is made to the program. BREAKPOINT allows the programmer to debug a FOR-TRAN program in an online interactive mode eliminating many of the time consuming recompiling and reloading operations.



A new "flat pack" vacuum fluorescent readout-the Digivac 2000 -has been developed by the Tung-Sol Division of Wagner Electric Corporation. Available in rectangular, low profile package, the Digivac 2000 incorporates the advantages of the Tung-Sol-developed cathodoluminescent readout (Digivac 1000) in a smaller package. The Digivac 2000 has a broad color spectrum which, with filters, can offer virtually any visible hue. Its low voltage, low current requirements make it directly compatible with all MOS IC logic packages.

Flexible language (alpha/numerical/symbolic) is a feature of this new product.

Circle #115 on Readers Service Card



# If You Heard 'Em Lucky, If You Didn't, Too Bad

These notices summarize recent SID chapter meetings, and are representative of the types of programs offered to members of SID chapters throughout the U.S.

# SAN DIEGO

January 8, 1974

- Speaker: John Silva, Ph.D., Naval Electronics Laboratory Center, San Diego.
- Topic: "Viewing Cardiac Performance Ultrasonically." A chemical equipment research effort to develop a non-invasive technique for diagnosing heart disease. Ultrasonic echocardiograms are recorded simultaneously with other types of cardiograms and pulse tracings, from patients. A computer program developed by NELC automatically derives key cardiac performance parameters from the recorded information. Parameters are a significant diagnostic aid and eliminate traumatic cardiac catharization.

# February 12, 1974

Speaker: Keith Bromley, Naval Electronics Laboratory Center.

Topic: Mr. Bromley, a research physicist, discussed and analyzed real time, programmable optical signal processors: in particular, a portable unit designed at NELC utilizing light-emitting diodes and charge coupled devices. A demonstration was performed.

# NEW YORK CITY

February 20, 1974

Speaker: Burt Masnick, Industrial Products Div., Hazeltine Corp. Topic: "Microprocessors and CRT

Displays." The logic design of an alphanumeric or mixed alphanumeric/graphics CRT display has traditionally been segmented along set lines. Various sections, such as keyboard control, memory, I/O handler, beam control and peripherals handler have been joined to form the total

lers.

January 11, 1974 terminal.

# LOS ANGELES January, 1974

Topic: Tour of Public Broadcasting Corp. TV Station KCET, Los Angeles.

How computers can help solve the problems that plague society is the topic of a new 575-page hardcover book, Computers and the Problems of Society, published by the American Federation of Information Processing Societies, (AFIPS), with which Society for Information Display is affiliated. Copies of the \$15.00 book can be ordered from AFIPS Press, 210 Summit Ave., Montvale, N.J. 07645.





Circle #114 on Readers Service Card

**Flat Pack Readout** 

logic package. The availability of low cost large capacity Read-Only Memories has enabled the design to utilize microprocessors as CRT display system control-

The various aspects of microprocessor design and the practical effects of the design choices available on the performance and capabilities of the display are the focus of considerable current interest.

# MINNEAPOLIS-ST. PAUL

Topic: Visit to Dynamic Information Systems, Inc., Lakeville, Minn. Description and demonstration of a mass memory bank involving microfilm vs. disc file equipment. The system also has editing-composing capabilities; copies; and serves as a computer

# **How Computers Can Help Society**

Program for '74 SID Symposium Page 17. **Registration Form**— **Reader's Service Card** 

# Calendar of Events

1974

April 1-6

17th International Electronic Components Exhibition. Exhibition Park, Paris, France

April 9-11

1974 International Optical Computing Conference (CompSoc). Zurich, Switzerland (Digests due February 1, 1974)

April 23-24

Workshop on Machine-Independent Graphics (ACM, NBS). NBS Headquarters, Gaithersburg, Md. April 24-26

Fifth Annual Pittsburgh Conference on Modeling and Simulation (ISA, Univ. Pittsburgh, Pittsburgh Sect.) Pittsburgh, Pa. (Abstracts due February 4, 1974)

May 6-10

National Computer Conference and Exposition. McCormack Place, Chicago, Illinois

May 21-23

15th International SID Symposium. Town & Country Hotel, San Diego, California

June 10-11

Chicago Spring Conference on Broadcast and Television Receivers (G-BTR, Chicago Sect.), Marriott Motor Hotel, Chicago, Ill. (Summaries due March 6, 1974)

October 9-10

1974 Conference on Display Devices and Systems. Co-sponsored with Group on Electron Devices, IEEE. Statler Hilton Hotel, New York City

# **SID** Proceedings: **Computer Graphics**

First Quarter Proceedings (Volume 15, No. 1) of the Society for Information Display, a special issue on Computer Graphics, includes articles on the following subjects:

The Technology and Characteristics of Computer Driven, Interactive, Graphic Display Systems; Computer Graphics Terminals-A Backward Look; Computer Graphics-The Present; Solid State Vertical Scale Instruments.

The issue may be ordered from SID National Office, 654 N. Sepulveda Blvd., Los Angeles, California 90049.

# **IEEE Display Devices' Call for Papers**

The 1974 Conference on Display Devices and Systems will be held on October 9-10, 1974 at the Statler Hilton Hotel, Seventh Avenue and 33rd Street, New York City, sponsored by the Electron Devices Group of the IEEE, the Society for Information Display, and the Advisory Group on Electron Devices.

# Previously Unpublished Papers -

The program will cover all of the disciplines relevant to research, development, and design of electronic display devices and systems. Previously unpublished papers describing significant new results of interest to active workers in the field are solicited. Among the areas of interest are: cathode-ray tubes, solid and liquid light emitters, gasdischarge devices, liquid crystals, electrochromics, light valves, projection displays, and utilization of IC technology. Related topics such as drive address and control techniques, phosphors, fiber optics, electron optics, photochromics, cathodochromics, image intensification and conversion, recording media directly applicable to displays, new phenomena, pertinent operational characteristics, measurement techniques, and new applications are to be included. Papers describing the interaction among display device performance. system requirements, and economic considerations relating to research, development, and design of displays are also invited.

The deadline for abstracts is June 24, 1974. The paper should be suitable for a 20-minute presentation, and authors are requested to submit both a 35-word abstract and a one-to-two-page draft summary. Since papers will be selected on the basis of the draft summary, this must include a concise statement of what new and significant results, differing from previous publications, have been obtained. Hand drawings and sketches may be included to aid in the selection of papers.

# **Specifications For Papers**

The 35-word abstract, suitable for publication in an Advance Program, should be typed on a separate sheet, and include title of talk, author's name, affiliation, complete address, and telephone number. Twenty copies of the draft summary and abstract must be submitted. The author's name, affiliation, complete address and telephone number must appear on the first page, with the author's name and abbreviated paper title on each subsequent page. Authors of ac-



SID renewal volume at the National Office is up this year. Pictured here diligently processing your renewal application is SID National Office Manager Vi Puff and temporary assistant, her daughter, Jane. As usual, some members wait until the last moment to send in their checks. How about you? Is your renewal in this picture? If not, don't wait. Send your check today for 1974 dues and enjoy a full year of SID benefits

cepted papers will be asked to prepare a final one-to-two-page summary (including figures) for publication in the Conference Program. A text of the full paper, with figures, for publication in the Conference Proceedings will be required by the last day of the Conference.

A few post-deadline papers (for 10-minute presentation) reflecting important new projects, will be considered if 100-word abstracts and one-to-two-page summaries with any pertinent illustrations, suitable for publication in the Conference Program, are received by September 16, 1974.

Mail all material to Thomas Henion, Palisades Institute, 201 Varick Street, New York, N.Y. 10014. Telephone: (212) 620-3384. Overseas authors are encouraged to send a single additional copy of their material directly to a convenient overseas committee member. If you have any questions concerning this announcement, please contact any one of the committee members.

# **Unique Liquid Crystal** Patented by RCA

An unusual form of liquid crystal, described as "an electronic window shade," has been patented by RCA Laboratories. The device is opaque until current is applied, at which time it opens to reveal whatever visual element is underneath.

The new liquid crystal undergoes a field-induced phase change upon application of low-powered current from an integrated circuit. The liquid crystal host material has an optically active cholesteric component. The electric field alters the texture of the liquid from a light-scattering to a transparent state, thus revealing the visual element. When the current stops it resumes its opaque condition. The developers of the device, Edward F. Pasierb and Chan Soo On both were associated with RCA Laboratories in Princeton, N.J.

RCA plans to open a liquid crystal plant in Franklin Township, N.J. to produce the new devices.

# Don't Miss the Boat

# Apply now for your '74 NCC "Everything Card"

If you missed the boat on the first annual National Computer Conference & Exposition last June, don't let it happen again. The first NCC in New York received accolades from attendees, exhibitors, and the media. The '74 NCC, even bigger and more comprehensive, will be held in Chicago's McCormick Place, May 6-10. And if you preregister before April 22, you'll be entitled to the '74 NCC Everything Card, your passport to all exhibits, program sessions, and a variety of special events.

You get much more with your Everything Card-special discounts for the NCC luncheons, your copy of the NCC Proceedings, plus the opportunity to make your hotel reservations at reduced convention rates. You'll also be in the running for a one-week trip for two from Chicago to Stockholm, Sweden for the IFIP Congress '74, August 5-10: or for one of five NCC lifetime registrations.

Just \$50 and the attached coupon is

all you need for your personalized

Everything Card. The '74 NCC brings it



all together, including: The world's largest display of computer hardware, software, peripherals, and services, presented by more than 250 exhibitors in over 800 booths. 
117 program sessions, focusing on computer science and technology and the appli-

My company is	interested in exhibiting a	at '74 NCC.			P	
Name	h	Title	)		+ 0°	ace, Chicag
Company						Ofmick Pi
Street				2	ery	-10.Mcc
City	Sta	te	Zip		Ш з	1 Apr

cations of data processing in 10 major user areas. 
Major addresses by prominent industry and professional leaders, including John D. deButts, Chairman of the Board of AT&T; C. W. (Clancy) Spangle, Executive Vice President of Honeywell Inc.: and George Glaser, AFIPS' President.

The '74 NCC is your one chance to examine virtually every data processing product and service at one time, in one place. You'll exchange information with 35,000 of your colleagues at the computer industry's single national forum for users, managers, and computer professionals. You'll be able to help solve your own specific data processing problems by evaluating competitive products firsthand. Many of these will be on display for the first time.

To receive your personalized Everything Card, plus complete housing information, send \$50 by check or money order with the preregistration coupon to '74 NCC, c/o AFIPS, 210 Summit Avenue, Montvale, New Jersey 07645.



Special Purpose Technology Corporation moves Cathode Ray Tube Operation into separate new, larger facilities. Company is set up to develop and manufacture complete line of CRTs from standard types to most sophisticated, including back ported, ultra high resolution, multi-neck, subscreen, and monoscopes. SPTC also designs, develops and manufactures display systems such as flying spot scanners, high-resolution monitors, fiber optic printers, computer terminals.

Program for '74 SID Symposium Page 17. **Registration Form—Reader's** Service Card—

# SIID Sustaining Members

ALLGEMEINE ELEKTRICITATS— GESELLSCHAFT AEG-Telefunken Vorstandssekretaruat 6 Frankfurt/Main-Sud West Germany AEG Hochhaus	PHOTO RESEARCH DIVISION KOLLMORGEN CORPORATION 3000 N. Hollywood Way Burbank, California 91505 NAC INCORPORATED 17 Kowa Bldg., No. 2-7 Nishiazabu 1-Chome Minato-ku, Tokyo, Japan
FEDERAL AND SPECIAL SYSTEMS	PHILCO-FORD CORPORATION
GROUP, ELECTRONIC	Palo Alto, California
COMPONENTS DIVISION	ELECTRONIC SYSTEMS DIVISION
Plainfield, New Jersey, 07061	RANK PRESCISION INDUSTRIES
CHERRY ELECTRICAL PRODUCTS	LTD.
CORP. 3600 Sunset Avenue	Sidcup, Kent, England
Waukegan, Illinois 60085	SIEMENS AG
CONRAC CORPORATION	Components Marketing
330 Madison Avenue	76 St. Martinstr.
New York, New York 10017	Munich, West Germany
DIACON, INC. 4812 Kearny Mesa Road San Diego, California 92111	SINGER-LIBRASCOPE Aerospace & Marine Systems Group 933 Sonora Avenue Glendale, California 91201
DuMONT ELECTRON TUBES	SYNTRONIC INSTRUMENTS, INC.
AND DEVICES CORPORATION	100 Industrial Road
750 Bloomfield Avenue	Addison, Illinois
Clifton, New Jersey 07015 FERRANTI ELECTRIC COMPANY Plainview, New York	TEKTRONIX, INC. Information Display Products P.O. Box 500 Beaverton, Oregon 97005
GML CORPORATION	THOMAS ELECTRONICS, INC.
594 Marrett Road	100 Riverview Drive
Lexington, Massachusetts 02173	Wayne, New Jersey 07470
HUGHES AIRCRAFT COMPANY	THOMSON-CSF
Culver City, California 90230	Paris, France
IBM CORPORATION	XEROX DATA SYSTEMS
Armonk, New York	El Segundo, California 90245

**Burroughs Now Making Displays in Mexico** 

In its first move to manufacture gas discharge display panels outside the U.S., Burroughs' Electronic Components Div. has begun production of Panaplex displays at its Guadalajara, Mexico plant, using half of a 200,000 sq. ft. complex for the present. At the start, only panels for calculators are being made, but this Fall Self-Scan alphanumeric panels also will be made. Observers said the move is expected to make Burroughs more competitive with LED and liquid crystal displays in the calculator and clock consumer markets.

# **Operational Amplifier**

Model 9734, from stock from Optical Electronics, Inc., is a modular operational amplifier said to provide lower offset voltage and lower offset voltage drift than obtainable from low cost integrated circuits. The 9734 is termed "a high performance, low cost FET operational amplifier for analog circuit and system designers."

Circle #116 on Readers Service Card

# Advertiser's Index

Burrough's Corporation	
<b>CELCO</b> (Constantine Engineering	
Labs. Co.)	
Comtal Corporation	
Constantine Engineering Labs.	
Co. (CELCO)	
Dumont Electron Tube & Devices . 13	
Electro-Science Labs., Inc12	
Ferranti Electric Inc	
General Electric	
Hughes Aircraft Company47	8
ISSEC	1
Keltron Corporation	1
Litton Industries, Inc	
Motorola/Ged	Ì
Optical Coating Laboratory, Inc 6	
Photo Research	
Polacoat, Inc	
Ramtek Corporation	
RCA	
Special Purpose Tube	ľ
Syntronic Instruments	
Systems Research 4	
Thomas Electronics	
Watkins-Johnson 5	
	Burrough's Corporation33CELCO (Constantine EngineeringLabs. Co.)41Comtal Corporation9Constantine Engineering Labs.9Constantine Engineering Labs.41Dumont Electron Tube & Devices13Electro-Science Labs., Inc.12Ferranti Electric Inc.37General Electric48Hughes Aircraft Company47ISSEC28Keltron Corporation42Litton Industries, Inc.36Motorola/Ged24, 25Optical Coating Laboratory, Inc.6Photo Research29Polacoat, Inc.34Ramtek Corporation16RCA15Special Purpose Tube28Syntronic Instruments2Systems Research4Thomas Electronics23Watkins-Johnson5

# Why horse around with words? Get the picture from Hughes.

Turning into the stretch, it's LUCKY LADY in front by one length. DANCING PRINCESS is second by a length and a half. On the inside, MISTER GEORGE is third by a head. In the middle of the track, FAST DRIVER. Here comes FAST DRIVER.

In the stretch it's LUCKY LADY in front...DANCING PRINCESS and MISTER GEORGE. And on the inside, FAST DRIVER. LUCKY LADY, DANCING PRINCESS and MISTER GEORGE. LUCKY LADY and DANCING PRINCESS. LUCKY LADY in front.

Down to the line of finish, it's LUCKY LADY and DANCING PRINCESS. And it's LUCKY LADY, the winner by a nose. DANCING PRINCESS is second by a length and a half in front of MISTER GEORGE.

The picture on the right says the same thing as the words on the left. But so much faster. And clearer. And when you consider the grow-

ina mountains of data you have to deal with, pictures become more a necessity than a luxury.

To answer the need in the burgeoning industrial and commercial markets, Hughes has used its high technology to develop advanced methods for the sensing, storage and display of pictorial data.

Now, this image processing tech-

nology has developed into a whole family of components, systems, subsystems and software. Our products include image memories, image processors,



Page 46 / SID Journal

UGHES AIRCRAFT COMPANY ISTRIAL PRODUCTS DIVISIO

Creative Image Processing.

special display systems, graphic terminals, direct view storage tubes, scan converter tubes, visible and IR sensors. We also have an applications

Compliments of Hollywood Park

engineering staff available to provide systems support and OEM assistance. (Both our products and our services can be tailored to your special requirements.)

Today, more than ever, Hughes is ready to help you get the picture. For a new Creative Image Processing Capabilities brochure, write: 6855 El Camino Real, Carlsbad, California 92008. Or call (714) 729-9191.